## NOTICE TO WATER WELL CONTRACTOR The original and first copy

## **MARI 3711**

WATER WELL REPORT

of this report are to be filed with the filed with the FCE WF SPATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the day JUN 7 - 1972

of well completion.

(Blease type or print)

(Blease type or print)

State Permit No. ....

STATE FILE RIFER	love this line)
(1) OWNER: SALEM. ORLUCK	(10) LOCATION OF WELL:
Name TIMOJEX Kalugen	County Mary-1012 Driller's well number
Address 1080784 Dre RFD 6	SE 14 NE 14 Section 2 T. 65 R. 2 W W.M.
Brooks oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	ByThe old Buildings
New Well □ Deepening □ Reconditioning ☑ Abandon □	+ Jim Ok During
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1 ` ´ .
Rotary D Driven D	Depth at which water was first found 105 = t. ft.
CableJetted   Domestic industrial Municipal	Static level 32 ft. below land surface. Date June 447
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded ID Welded ID Welded ID Welded ID Welded ID Welded ID Welded ID	
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
DEDUCE A MYONG	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? The No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used STAY	MATERIAL From To SWL
Size of perforations / ½ in, by 3 c in,  2.50 perforations from 10.5 ft. to 12.9 ft.	Existing well 105 ft
perforations fromft. toft.	Palled in sone Pin det
perforations fromft, toft.	Villa January Grand
	1065e graves 105 107
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	ament gravel 107 119
Manufacturer's Name	Loose gravel .119 130 32
Type Model No	Blue 0124 130
Diam. Slot size Set from ft. to ft.  Diam. Slot size Set from ft. to ft.	
Diam, Slot size Set from 11, to 11.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? The I No If yes, by whom? By//er	
Wield: /80: gal./min. with 20 ft. drawdown after 31/4 hrs.	
gai./min. with it. drawdown arter irs.	
" " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Antesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started May 3/19 Completed Jane 4 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well forc 5 1972
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] John W Dest Date June 5, 1972
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 41.3.7
Number of sacks of bentonite used in well seal sacks	Drining Wachine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Dres No Plugs Size: location ft.	Name Charles Seck Well drill 1995
Did any strata contain unusable water?  Yes No	(Person, firm or corporation) (Type or print)  Address //D, SKy/cme. 12- Canby Ore
Type of water? depth of strata	Address 1 1 y 10 1 y 10 10 c. 17 C. G. That J. C. T.
Method of sealing strata off	[Signed] to kn W Usek
Was well gravel packed?   Yes   No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. H.4. 7. Date June 4, 1972
	<del></del>