

The original and first copy of this report are to be filed with the

RECEIVED JUN 16 1972

WATER WELL REPORT

3718 MARI.....

State Well No. 65/2W-2ad

STATE ENGINEER, SALEM, OREGON 97310

STATE OF OREGON

(Please type or print)

State Permit No.

within 30 days from the date of well completion.

(Do not write above this line)

(1) OWNER:

Name Peter Kalugin
Address Rt 1 Box 151 Merdis Ore

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [x] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal []
Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 138 ft. Gage 277
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [x] Yes [] No.
Type of perforator used Star
Size of perforations 3/8 in. by 1 1/2 in.
300 perforations from 110 ft. to 130 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [x] Yes [] No If yes, by whom? Driller
Yield: 191 gal./min. with 27 ft. drawdown after 4 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Amount of Puddled clay
Well sealed from land surface to 40 ft.
Diameter of well bore to bottom of seal 11 1/2 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 1 1/2 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [x] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [x] Yes [] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [x] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
3E 1/4 NE 1/4 Section 2 T. 6 S R. 2 W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 105 ft.
Static level 35 ft. below land surface. Date 6-12-72.
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 138 ft. Depth of completed well 138 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: TOP soil, Brown silt & clay, Brown silt, Brown clay, Dark Brown clay, Blue sand, Blue clay, Cement gravel, Free gravel, silt & clay, Blue clay.

Work started June 6 1972 Completed June 17 1972
Date well drilling machine moved off of well June 14 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used, and information reported above are true to my best knowledge and belief.
[Signed] John W Beck Date June 14, 1972
(Drilling Machine Operator)
Drilling Machine Operator's License No. 337

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name J W Beck Well Drilling
(Person, firm or corporation) (Type or print)
Address 1109 Kylan Dr Canby Ore 97013
[Signed] John W Beck
(Water Well Contractor)
Contractor's License No. 449 Date June 14 1972