

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT MAY 26 1969 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

3721 MARI... G-4908

State Well No. 6/2 W-2 bdd State Permit No.

(1) OWNER:

Name MRS. DONALD STILL Address RT # 3, BOX 954 SALEM, OREGON 97302

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED:

8" Diam. from 0 ft. to 120 ft. Gage 250

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used MILLS Size of perforations 3/8 in. by 160 perforations from 112 ft. to 118 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 23 ft. below land surface Date 5/12/69 Man pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom Stettlons Yield: 540 gal./min. with 72 ft. drawdown after 3 hrs. 650 " 100 " 3 " 700 " 118 " 3 " Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 54° Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used PUDDLE CLAY Depth of seal 25 ft. Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [] Yes [X] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County MARION Driller's well number 1/4 Section 2 T. 6 S. R. 2 WEST W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing Depth drilled 120 ft. Depth of completed well 120 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include TOP SOIL, BROWN CLAY, BROWN SILKY SAND, BLUE CLAY, GREY SAND, BLACK SAND, BLUE CLAY, GREY SAND, GRAVEL WATER BEARING.

Work started 5/7 19 69 Completed 5/22 19 69 Date well drilling machine moved off of well 5/12 19 69

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] J. F. Terrell Date 5/24, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 179

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME J. F. TERRELL WELL DRILLING (Person, firm or corporation) (Type or print)

Address RT # 1, BOX 57, GERVAIS, OREGON

[Signed] Mrs. Zona D. Terrell (Water Well Contractor)

Contractor's License No. 460 Date 5/24, 1969