filed with the JUN2 - 1971	L REPORT OREGON State Well No.	6/2W-2da	
STATE ENGINEER, SALEM, OBEGON 97310 ENGINEER STATE STATE ENGINEER, SALEM, OBEGON 97310 ENGINEER STATE	State Permit N	•	
of well completion. SALEM. OF Co not write ab She learing Oaks Revery Faving Inc.	bove this line) $65797 - 6579$	17	
	(10) LOØATION OF WELL:		
(1) OWNER:			
Name Afra Hohly	County MARION Driller's well number		
Address 10807 -87 TH ALIE. N. E.	1/4 Section 2 T. C. S		
(a) MYDE OF WODK (about).	Bearing and distance from section or subdivis	ion córner	
(2) TYPE OF WORK (check):			
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	1-2		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 60 ft.		
Rotary Driven Domestic Dindustrial D Municipal D	Static level 25 ft. below land surface. Date 5-/7-7		
Cable Jetted			
Dug Bored D Trigation Prest Well Other D			
CASING INSTALLED: Threaded Welded 1. Welded 2. Compared to 1. Compared 1. Welded 2. Compared 1. Compar	(12) WELL LOG: Diameter of well Depth drilled 20/ ft. Depth of comp	oleted well 19/ ft.	
ft. toft. Gage	and show thickness and nature of each stratu	ım and aquifer penetrated,	
	with at least one entry for each change of forms position of Static_Water Level and indicate prin		
PERFORATIONS: Perforated? Yes No.			
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by 2 in.	Soil	02	
240 perforations from 107 ft. to 110 ft.	BROWN - CHAY	2 24	
336 perforations from 173 ft. to 187 ft.	11 - 11 HERALI	24 27	
perforations fromft, toft.	1/ 1/	29 51	
	Bhurs - 11	5158	
(7) SCREENS: Well screen installed? Yes No	GEAV - SANDY CLAY	58 68	
Manufacturer's Name	RLOS - CHAY	68 84	
TypeModel No.	BRAWN - 114	84 102	
Diam. Slot size Set from ft. to ft.	BLACK - SAND + GRAMA	102 117	
Diam. Slot size Set from ft. to ft.	BLUM - Chay	117 141	
(2) WELL TECTS. Drawdown is amount water level is	BLACK - SAND	141 146	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level.	VERAY - Chay	145 163	
Was a pump test made? Yes \(No If yes, by Mother Parks	- BROWN - PACKED SAND	163 166	
Yield: 500 gal./min. with 14 ft. drawdown after 4 hrs.	BLACK - SAND+GRAVAL	166 187	
" " " "	Blue - Chay	180 201	
# · · · - # # N	on a Report description of the second of th		
AL THE STATE OF TH	and the second s		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m			
Temperature of water Depth artesian flow encountered ft.	Work started \$7-3- 197/ Complete	ted 5-17 - 197/	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5-19- 1971	
Well seal-Material used DEILING HOUD + COTTINGS	Drilling Machine Operator's Certification		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision.	
Diameter of well bore to bottom of sealin.	best knowledge and belief	, above are wat to my	
Diameter of well bore below sealin.	[Signed] Will tout	Date 5-19 192/	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	_	
Number of sacks of bentonite used in well sal sacks	Drilling Machine Operator's License No.	310	
Brand name of bentonite	W.A. W.N Control Control		
Number of pounds of bentonite per 10 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisd true to the lest of my knowledge and be	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ✓ Yes ☐ No Plugs Size: location ft.	Marile 1 1 1 act		
Did any strata contain unusable water? Tyes No	Name (Person, firm or corporation)	Type or print)	
	Address 5545 Vester	JA SE	
Type of water? depth of strata	Address	A.	
Method of sealing strata off	[Signed] Leven K. Kirl	4-4	
Was well gravel packed? Yes No Size of gravel:	(Water Well Cont		
Gravel placed from ft_ to ft.	Contractor's License No Date	5-19- , 19.2/	