WATER WELL REPORT NOTICE TO WATER WELL CONTRACTOR
The original and first copy The original and first copy of this report are to be filed with the

State Well No. 6/26-2

STATE OF OREGON
(Please type or print) G-3892 STATE ENGINEER, SALEM, OREGON 97310 . within 30 days from the date of well completion.

of well completion.	G-3892 State Permit No.
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Joe Zellner	Was a pump test made? Yes No If yes, by whom? Driller
Address Route 1, Box 149	Yield: gal./min. with ft. drawdown after hrs.
Gervais, Oregon	<u>250 " 20 " 1 "</u>
(2) LOCATION OF WELL:	400 "27 " 3 "
	Bailer test gal./min. with ft. drawdown after hrs.
County Marion Driller's well number	Artesian flow g.p.m. Date
½ ½ Section T. R. W.M.	Temperature of water Was a chemical analysis made? ☐ Yes ▼ No
Bearing and distance from section or subdivision corner	(40) 77777 7 0 0
500 ft, W,& 1500 ft N, of S.E. cor	Districted of from Notions Capital manufacturing
of sec 2, T.6.S. R.2W.	Depth drilled 225 ft. Depth of completed well 225 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
3846	stratum penetrated, with at least one entry for each change of formation.
(3) TYPE OF WORK (check):	MATERIAL FROM TO
777 77 78W	Top soil brn. 0 1
New Well X Deepening   Reconditioning   Abandon	Clay brn. 1 17
andonment, describe material and procedure in Item 12.	Sand brn fine. 17 55
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sandy clay, grey. 55 106
Rotary C Dutron C	Med conglom, grey, hard. 106 117
Irrigation Test Well □ Other □ Cable □ Jetted □	Sandy clay, grey. 117 162
Dug  Bored	Med conglom, grey, hard. w.b. 162 185
(6) CASING INSTALLED: Threaded Welded	Med sand, with small gravel. 185 198
8 " Diam. from 200 0 ft. to 223 ft. Gage 250	Med conglom, grey, hard. w.b. 198 208
" Diam. fromft. toft. Gage	Sandy glay, grey. 208 212
"Diam. from	Med conglom, grey, loose, w.b. 212 225
(7) PERFORATIONS: Perforated? XYes \( \square\) No	
Type of perforator used M1118	
Size of perforations in by 3 in.	
24.0 perforations from 165 ft. to 185 ft.	
96 perforations from 200 ft. to 208 ft.	
120 perforations from 212 ft. to 222 ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes ■ No	
Manufacturer's Name	
Time Model No.	
Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	Work started 8-6-66 19 Completed 8-19-66 19
	Date well drilling machine moved off of well 8-19-66
(9) CONSTRUCTION:	(13) PUMP:
Well seal-Material used in seal Bentonite & cuttings	Manufacturer's Name Jacuzzi
Depth of seal 18 ft. Was a packer used? NO	- Girh
Diameter of well bore to bottom of seal 13 in.	Type: H.P.
Were any loose strata cemented off? Tes A No Depth	Water Well Contractor's Certification:
Was a drive shoe used? Yes No	This well was drilled under now invitation
Was well gravel packed? ☐ Yes Z No Sip of gravel:	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME R Stadeli & Sons
Did any strata contain unusable water? Tes X No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt # 3. Box 169 Silverton
Method of sealing strata off	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 16 - 322
-	[Signed] Paul Q. Stadeli
Static level 57 ft. below land surface Date 8-19-66	[Signed] (Water Well Contractor)
Artesian pressure lbs. per quare inch Date	Contractor's License No. 296 Date 8-27-66 19
= - (USE ADDITIONAL SH	EETS IF NECESSARY)