The original and first day L SEP 16 1971

STATE OF OREGON

State Well No.

STATE ENGINEER, SALEM OF AND ENGINEER (NEEP lease type or print) within 30 days from the date

of well completion. SALCIVI OF (Bo not write an	ove this line) Wi	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Ray Zorn	County Marion Driller's well numb	er 1578
Address 11220 Portland Road NE Salem, Ore	14 14 Section 3 T. 6S R.	2W W.M.
	Bearing and distance from section or subdivision	corner
(2) TYPE OF WORK (check):	Vi.	
New Well ☐ Deepening ■ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary   Driven   Domestic   Industrial   Municipal	Static level 36 ft. below land surface. Date 9-11-71	
Cable	Artesian pressure 1bs. per square inch. Date	
CASING INSTALLED: Threaded □ Welded 2	(12) WELL LOG: Diameter of well below casing	
6 "Diam from 120 ft to 130 ft Gage 250	Depth drilled 10 ft. Depth of completed well 130 ft.	
"Diam from ft. to ft. Gage ft. to ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
"Diam, from It. 10 It. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal	ıl water-bearing strata.
Type of perforator used	MATERIAL F	rom To SWL
Size of perforations in. by in.		20 130
perforations fromft. toft.		
perforations from ft. to ft.		
perforations fromft. toft.		-
(7) SCREENS: Well screen installed?  Wes West Screen installed?  West Screen installed?		
Manufacturer's Name Model No	The second secon	
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
E#		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes 🍱 No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" " "		
H H H		
Bailer test 20 gal./min. with 15 ft. drawdown after 1 hrs.	TWO TO A SHARE A TOTAL TOTAL TAY AS LIST TAKEN A LINE LIGHT.	
Artesian flow g.p.m.	-	-
perature of water Depth artesian flow encounteredft.	Work started 9-10-71 19 Completed	9_11_71 19
perutate of water	Date well drilling machine moved off of well	
(9) CONSTRUCTION:		9-11-71 19
Well seal-Material used	Drilling Machine Operator's Certification: This well was constructed under my di	
Well sealed from land surface toft.	Materials used and information reported ab	ove are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Grada W Morton Date 9-14-71, 19	
Number of sacks of cement used in well sal sacks	Drilling Machine Operator's License No. 536	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per logalions of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is	
of water	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Wes \( \subseteq \text{No} \)	Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)	
Type of water? depth strata	Address 7641 35th Ave. NE Salem Oregon 97303	
	SI DO DE	
Method of sealing strata off  Was well gravel packed? □ Yes ▼No Size of gravel:	[Signed] (Water Well Contractor)	
	Contractor's License No2 Date _9_1.	
Gravel placed fromft.	, Date	1y