NOTICE TO WATER WELL CONTRACTOR WATER WELL REPORTECEIVED The original and first copy of this report JAN 30 1978 tate Well No. 65 2W-3 are to be filed with the STATE OF OREGON WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 (Please type or print) within 30 days from the date (Do not write above this Hat ER RESOURCESta DEPThit No. of well completion. SALEM. OREGON (1) OWNER: (10) LOCATION OF WELL: Name Mrs. H. F. Caughlin Address 11094 71 Avenue NE County Marion Driller's well number 2111 34 Section 3 т. 6S R. X 2W Salem, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning [New Well IV Deepening [Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 65 Rotary Driven 🛘 Domestic | Industrial | Municipal | Static level 35 ft. below land surface. Date12/10/77 Cable Jetted 🔲 Irrigation 🔯 Test Well 🗌 Other Dug Bored | Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | X (12) WELL LOG: Diameter of well below casing 8 "Diam from LOD ft. to 190 ft. Gage 250 Depth drilled ft. Depth of completed well 190 _____ft. Gage _____ Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Y Yes No. Type of perforator used Mills Knife MATERIAL. Size of perforations 3/8 in. by 2 Topsoil 0 perforations from 120 __ft. to 133 Yellow Clav 2 32 perforations from \$33 180 ft. to 189 Blue Clay 32 65 perforations from _____ ft. to _____ Black Sand 65 81 Blue Clav 81 117 (7) SCREENS: Well screen installed? | Yes | No Black Sand and Gravel **£117** 133 Manufacturer's Name Blue Clay 133 175 ... Model No. ... Black Sand and Gravel Diam. Slot size Set from ... Diam. Slot size Set from (8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? W Yes D No If yes, by whom? driller Yield: 500 gal./min. with 19 ft. drawdown after 3 hrs. gal./min. with Bailer test ft. drawdown after Artesian flow g.p.m. perature of water 53 Depth artesian flow encountered Work started 11/17/77 19_ Completed 12/10/97 Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal—Material used Portland Cement Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Well sealed from land surface to 19 ft. Materials used and information reported above are true to my Diameter of well bore to bottom of seal ______in. best knowledge and belief. [Signed] And M. Mortun Date 12/10/77, 19..... Number of sacks of cement used in well seal 10 Drilling Machine Operator's License No. ____536 How was cement grout placed? poured in from the top Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? N Yes No Plugs Size: location ft. NameWillamette Drilling Co.
(Person, firm or corporation) (Type or print) Did any strata contain unusable water? 🗌 Yes 🗶 No [Signed] Dallas (Water Well Contractor) Type of water? Method of sealing strata off Was well gravel packed? Yes Y No Size of gravel: Contractor's License No. <u>561</u> Date <u>12/10/77</u>, 19

ft_to ft.

Gravel placed from