WATER WELL REPORT

6/2	w	14.	81	1)
			~~~~~~ <i>\</i> '	١./

NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM 10, OREGON
within 30 days from the date
of well completion.

STATE OF OREGON (Please type or print)

Štate Well No. .. G 5835 state Permit No.

(1) OWNER: Jam Watts	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Cak Crest Farm	Was a pump test made?   Yes No If yes, by whom?		
Address 2770 Wallace Rd NW	Yield: gal./min. with ft. drawdown	after hrs.	
Salem, Ore.	"	. 37	
(2) LOCATION OF WELL:	33 33	***************************************	
County Marion Driller's well number 6/2W-11B	Bailer test gal./min. with ft. drawdown	after hrs.	
1/4 1/4 Section T. R. W.M.	Artesian flow g.p.m. Date	· · · · · · · · · · · · · · · · · · ·	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis ma	de? 🗌 Yes 📙 No	
	(12) WELL LOG: Diameter of well below cas	ing 12	
,	Depth drilled 208 ft. Depth of completed well	A	
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each character.	and structure, and	
		FROM TO	
(3) TYPE OF WORK (check):	Top soil	0 2	
Well Well Deepening Reconditioning Abandon		2 20	
andonment, describe material and procedure in Item 12.	_Clay blue	20 50	
(A) DROBOGED TYGE ( I . I )	Fine sand & claw	50 75	
(4) PROPOSED USE (check): (5) TYPE OF WELL	Clean blk sand	75 0/1	
Domestic   Industrial   Municipal   Rotary   Driven   Cable	_Clay grey	ol 106	
Irrigation Test Well   Other   Dug   Bored	Gravel with clay	106 126	
(A) CLACITYC TYTCHATT TIP	Sand & gravel (clean)	126 139	
(6) CASING INSTALLED: Threaded ☐ Welded  12. 3/4Diam. from 1=0	O	139 1/1/1	
	I Fine sand with clay	1/1/1 169	
"Diam, fromft. toft. Gage		169 179	
"Diam, from	Fine silty sand	179 189	
(7) PERFORATIONS: Perforated?	Sand & gravel (clean)	189 208	
Type of perforator used Mills			
Size of perforations 5/6 in. by 2 in.	_	<del></del>	
230 perforations from 127 ft. to 138 ft. to 205 ft.	t.		
	<u>i</u>		
perforations fromft. tof	· •		
perforations fromft, tof			
perforations fromft. tof			
(8) SCREENS: Well screen installed   Yes  No			
Manufacturer's Name			
Model No.	met .		
Slot size Set from ft. to f	Work started 5/20 19 63 Completed 6/	4/63 19	
Diam. Slot size ft. to f	Date well drilling machine moved off of well 6/4	/63 19	
(9) CONSTRUCTION:	(13) PUMP:		
Pontanita 2 1			
Well seal Material used in seal Deflution 3 8K8.  Depth of seal ft. Was a packer used? NO	Manufacturer's Name	***************************************	
Diameter of well bore to bottom of seal	Type:	P	
Were any loose strata cemented off?   Ves No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? X Yes \( \subseteq \text{No.} \)	This well was drilled under my jurisdiction an	.d this	
Was well gravel packed?  Yes No Size of gravel:	true to the best of my knowledge and belief.	id this report is	
Gravel placed fromft_toft.	NAME Harry A. Robinson		
Did any strata contain unusable water? Tyes I No	(Person, firm or corporation) (Tyr	pe or print)	
Type of water? Depth of strata	Address 2214 Front St. NE Sele	m, Ore.	
Method of sealing strate off		,	
(10) WATER LEVELS:	Drilling Machine Operator's License No		
Static level 22 ft below land surface Date 6/4/63	[Signed] (Water Well Contractor)		
Artesian pressure lbs per square inch Date	Contractor's License No. 22 Date 6/8	162	
ing Del adama	Contractor's License No. 22 Date 6/8	/	