NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM. OREGONEOUS TE FNCINCEP

State Well No. 6/2w-44

State Permit No.

illed with the	CALCINICED	
TATE ENGINEER, SALEM, OREGON	FIRST TE ENGINEATER OF OREG	ON
within 30 days from the date	SALEM. OREGEMese type or prin	ıt)
of well completion.	SALEM, ORLOGI.	

G-3933

1) OWNER:	(11) WELL TESTS: Drawdown is amount w	ater level is	
ame FRED GOLDSMITH	Was a pump test made? Xyes \(\text{No If yes, by whom?} \)		
ddress 66II S.W. OAK STREET	Yield: 500 gal./min, with 33 57 drawdown		
PORTLAND. OREGON ZIP 97233	" 188 450 " 47 "	I2 "	
2) LOCATION OF WELL:	<u>" 400 " 43 "</u>	IŽ "	
**************************************	RAMAE test 350 gal./min. with 35ft. drawdow	m after I2 hrs.	
ounty MARION Driller's well number II84	Artesian flow g.p.m. Date		
34 34 Section 4 T. 6 5 R. 2 W W.M.	Temperature of water Was a chemical analysis ma	ade? 🗌 Yes 📋 No	
earing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casi	ng	
	B4- 3 200 % B4	200 ft.	
	Depth drilled 200 ft. Depth of completed well		
	Formation: Describe by color, character, size of material a show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	e material in each	
	- MATERIAL	FROM TO	
3) TYPE OF WORK (check):	TOP SOIL	0 3	
Well Deepening Reconditioning Abandon	YELLOW CLAY	3 I6	
andonment, describe material and procedure in Item 12.	BROWN CLAY	I6 35	
4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAY CLAY	35 75	
Rotary Cl Driven Cl	BLACK SAND	75 I20	
Cable W Jetted	CEMENTED BLACK SAND & GRAVEL	I20 I36	
rigation Test Well Other Dug Bored	GRAY CLAY	I36 I60	
6) CASING INSTALLED: Threaded Welded X	BLACK SAND	I60 I80	
10 "Diam from TOP ft. to 200 ft. Gage 250	BLACK SAND & GRAVEL	180 200	
"Diam. from			
and the second s			
3.5777 Tr. (%			
ize of perforations 2 in. by 3/8 in.			
230 perforations from			
200 Ta5 200		<u> </u>	
perforations from ft. to ft. to ft. to ft.			
perforations fromft. toft.			
8) SCREENS: Well screen installed? Yes Xno			
Manufacturer's Name			
Model No.			
Slot size Set from ft. to ft.	Work started OCT IO 1966 Completed NOV	I7 I966	
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well NOV I		
9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal & PUDDLE CLAY	Manufacturer's Name		
Depth of seal 20 f. Was a packer used?	Type: H.P.		
Diameter of well bore to bottom of sealin.	1.		
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 🛣 Yes 🗌 No 🍱	This well was drilled under my jurisdiction an	d this report is	
Was well gravel packed? Tyes Y No Size of gravel:	true to the best of my knowledge and belief.	a min report is	
Gravel placed fromft_oft.	NAME WILLAMETTE DRILLING CO		
Did any strata contain unusable water 📋 Yes 📋 No	(Person, firm or corporation) (Type	or print)	
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, ORE	GON	
Method of sealing strata off	Drilling Machine Constants It		
(10) WATER LEVELS:	Drilling Machine Operator's License No. 474		
Static level 30 ft. below land surface Date II. 17/66	[Signed] Consil O, Seiler)	
Static level ft. below land surace Date Artesian pressure lbs. per quarench Date	Contract NOV 17	I966	
(USE ADDITIONAL SH	Date		
, , ,	/m/		