NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

Gravel placed from ..

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## STATE OF OREGON JULI 6 1974 State Well No. 65/2W-5 (Please type or print) STATE WATER WELL REPORT GEIVED

(Please type or print) STATE ENGINEERState Permit No.

(Do not write above this line ALEM. OREGON Corr per repair log

(1) OWNER:	(10) LOCATION OF WELL:
Name Robert E. Taubman	County Marion Driller's well number 1841
Address 2153 SW Main Street	14 14 Section 5 T. 6.S R. 2.7 W.M.
Portland, Oregon	Bearing and distance from section or subdivision corner
2) TYPE OF WORK (check): Repair	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
totary   Driven   Domestic   Industrial   Municipal	Static level ft. below land surface. Date
Cable     □     Jetted     □     Intrigation     □     Test Well     □     Other     □	Artesian pressure lbs. per square inch. Date
CASING INSTALLED:       Threaded □       Welded □         6       " Diam. from top ft. to st. Gage 250         " Diam. from ft. to ft. Gage "Diam. from ft. to ft. Gage "To Diam. ft. to ft. Gage "To Diam. ft. G	(12) WELL LOG: Diameter of well below casing  Depth drilled 107 ft. Depth of completed well ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Brown Top Soil 0 2
perforations from ft. to ft.	Brown silty clay 2 27
perforations from	Gray Silty Clay 27 82 82 81 81 82 92
perforations from ft. to ft.	
7) SCREENS: Well screen installed? ☐ Yes ☑ No	Open cavity (filled with
Manufacturer's Name	Black sand and gravel 107
TypeModel No	Black sand and gravel 107
Diam, Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
	Note: Drilled 6" conductor hale to this
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	12" well that was drilled July 5, 1973
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	To feed gravel to help clear up the said.
gal./min. with ft. drawdown after hrs.	
" " "	
" " "	
<u> </u>	
Bailer test gal./min. with ft. drawdown after hrs.	
esian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started June 11 19 7/4 Completed June 18 19 7/4
(9) CONSTRUCTION:	Date well drilling machine moved off of well June 18, 1974, 19
Well seal—Material used <u>Cement</u> Well sealed from land surface to <u>20</u> ft.  Diameter of well both to bottom of seal <u>10</u> in.	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Daily Date June 12, 19.74.
Number of sacks of cement used in well seal	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ⊠ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?  Yes No	Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 7641 35th Ave. NE Salem, Oregon
Method of sealing strata off	E - DO Rains
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 2 Date June 18, 1974, 19