

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

MARI 3793
WATER WELL REPORT

3793
MARI

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON

State Well No. 65/2W-5

RECEIVED

(Please type or print)
(Do not write above this line)

State Permit No.

SEP-6-1977

(1) OWNER:

WATER RESOURCES DEPT.

Name Ernest L. Zielinski SALEM, OREGON
Address 5270 Hazelgreen Rd. NE
Salem, Oregon ~~97310~~ 97303

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

(4) PROPOSED USE (check):

Rotary Driven
Cable Jetted
Dug Bored
Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
12" Diam. from top ft. to 215 ft. Gage 2.50
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used Mills knife Perforator
Size of perforations 3/8 in. by 2 3/4 in.
288 perforations from ~~188~~ 188 ft. to 200 ft.
312 perforations from 105 ft. to 126 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? Yes No If yes, by whom? driller
Yield: 750 gal./min. with 12 ft. drawdown after 5 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland ~~C&C~~ Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 17 1/2 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 21 sacks
How was cement grout placed? poured in from the top

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 2067
1/4 1/4 Section 5 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 78 ft.
Static level 43 ft. below land surface. Date 7/21/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 215 ft. Depth of completed well 215 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sticky Blue Topsoil	0	1	
Sticky Blu Clay	1	78	
Blue Clay and Sand	78	80	
Black Sand	80	98	
Black Sand and Gravel	98	126	
Blue Clay	126	147	
Black Sand	157	156	
Blue Clay	156	179	
Black sand and Gravel	179	200	
Brown Clay	200	205	
Black Sand and Wood	205	213	
Black Sand and Gravel	213	215	

Work started 7/11/77 19 Completed 7/21/77 19
Date well drilling machine moved off of well 7/21/77 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Dallas R. Davis Date 7/22/77, 19.....
(Drilling Machine Operator)

Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 1450 Barnick Rd. NE Salem, Oregon 97303

[Signed] Dallas R. Davis
(Water Well Contractor)

Contractor's License No. 561 Date 7/22/77, 19.....