NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTS

AUG 2 197 State Well No.

MARI 3794

65/2W-5

Corr per repair log (1) OWNER: (10) LOCATION OF WELL: Driller's well number 1744 EXEX Robert E. Taubman Name 2153 SW Main Street W.M. 14 Section 5 68 214 Portland Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Deepening [Reconditioning [Abandon | New Well 17 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 101 Rotary Driven | ft. below land surface. Date 7_6_73 Domestic | Industrial | Municipal | Static level X Cable Jetted Irrigation 図 Test Well □ Other Oug Bored Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [(12) WELL LOG: Diameter of well below casing ... 12 " Diam, from top ft. to 260 ft. Gage 250 Depth drilled ft. Depth of completed well" Diam. from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. , PERFORATIONS: Perforated? Tyes I No. MATERIAL. From Type of perforator used Mills Size of perforations 7/16 in. by Top Soil Ω 2 72 perforations from 101 ft. to 106 Brown silty clay 27 121 137 perforations from Gray sflty clay 32 99 912 perforations from 189 Blue Sticky Clay 82 99 .06 Black and and gravel (7) SCREENS: Well screen installed? 🗆 Yes 🏗 No 106 117 <u>Grav sandv clav</u> Manufacturer's Name Brown cemented sand and grave 117 137 Blue gravelly clay 137 Diam. Slot size Set from ft. to ft. **EXMONITIONAL EXPERSE** XXXXXDiam. Slot size Set from ft. to 149 Gray sandy clay ክፍና Blue Gravelly Clay 166 79 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Grav sandy clay 179 1.85 Was a pump test made? ™ Yes □ No If yes, by whom? Driller 185 220 Blue gravelly clay 300 gal./min. with 32 29 hrs. Brown gravelly clay ft. drawdown after 400 37 same " 500 45 same " same hrs. 600 gal./min. with Bailer test rsian flow erature of water برين Depth artesian flow encountered ft. Work started June 9, 19 73 Completed July 5, 73 19 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Cement and Puddle Clay This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore below seal ______in. Date July 6, 19.73. Number of sacks of cement used in well seal _____sacks Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name	WILL	AMETTI	a DRT	LLIN	G. COMPA	NTV		
		rson, firm		(Type or print)				
Address	7641	35th	Ave	NE	Salem.	Oregon		
	G	7	· D	1	50'	-) -0		
[Signed]		m	//	<u>() </u>	and le	<u> </u>		
	Emil D. Bull. (Water Well Contractor)							

Contractor's License No. 2 Date July 6, 1973 19.....

......lbs./100 gals.

Was a drive shoe used? ∑ Yes □ No Plugs Size: location ft.

depth of strata

Did any strata contain unusable water?

Yes
No

Gravel placed from ft. to

Was well gravel packed? ☐ Yes No Size of gravel:

Type of water?

Method of sealing strata off

This is to replace the log sent to you in the mame of Carl Ditchen, job #1744, Mr. Ditchen just farms this land and Taubman owns it, this was an error our part.

Willamett Drilling Company



SUPERSEDED

NOTICE TO WATER WELL CONTRACTOR (The original and first copy of this report are to be filed with the

WATER WELL REPORTJUL I 01973

(Do not write above this line)

STATE OF OREGONATE ENGINEER Well No. (Please type or print) SALEM OREGSTate Permit No. ..

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:					
Name Carl Ditchen	County Marion Driller's well no	ımber	1744	<u>'</u>		
Address Rt. 2 Box 254 Silverton, Oregon	½ ½ Section 5 T. 6S	R. 2W		W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner	:			
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.						
	(11) WATER LEVEL: Completed w	ell.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	1()1	ft.		
Rotary Driven Domestic Industrial Municipal	Static level 28 ft. below land surface. Date 7-6-73 Artesian pressure lbs. per square inch. Date					
Dug Bored Irrigation Test Well Other						
CASING INSTALLED: Threaded ☐ Welded ☐	(12) WELL LOG: Diameter of well below casing					
" Diam. fromft. toft. Gage	Depth drilled 260 ft. Depth of completed well 260 ft.					
	Formation: Describe color, texture, grain size a and show thickness and nature of each strature					
	with at least one entry for each change of format	tion. Repo	rt each	change in		
PERFORATIONS: Perforated? ☑ Yes ☐ No.	position of Static Water Level and indicate prin	cipai wat		_		
Type of perforator used Mills	MATERIAL	From	То	SWL		
Size of perforations 7/16 in. by 2 3/4 in.	Top Soil	0	_2_			
72. perforations from 1012. 36. ft. to	Brown silty Clay	2	27			
228 perforations from 121 ft. to 137 ft.	Gray Silty Clay	27	82			
912 perforations from 189 ft. to 257 ft.	Blue Sticky Clay Black sand and gravel	82 99	99 106			
(7) SCREENS: Well screen installed? Yes 17 No	Gray sandy clay		117			
Manufacturer's Name	Brown cemented sand and grave		137			
Type Model No	Blue Gravelly Clay		149			
Diam Slot size Set from ft. to ft.	Gray sandy clay		166			
Diam Slot size Set from ft. to ft.	Blue Gravelly clay	166	179			
(8) WELL TESTS: Drawdown is amount water level is	Gray sandy clay	1 1	185			
10 Met ed pelow Static level	Blue Gravelly clay	1 1	220			
Was a pump test made? Tyes No If yes, by whom?	Brown gravelly clay	220	_260_			
id: 300 gal./min. with 32ft. drawdown after 20 hrs.		1		-		
400 " 37 " same"						
<u>"</u> 500 " 45 " same"						
Railerxtest 600 gal./min. with 53 ft. drawdown after Samars.						
rsian flow g.p.m. 62 same						
perature of water Depth artesian flow encountered ft.	Work started June 9, 1973 Complete	ed Juil	y 5,	73 ¹⁹		
(9) CONSTRUCTION:	Date well drilling machine moved off of well J	ılv 5,	19 7 3	19		
Well seal—Material used Cement and Puddle Clay	Drilling Machine Operator's Certification:					
Well sealed from land surface to	This well was constructed under my					
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above a	are irue	: to my		
Diameter of well bore below seal12 in.	[Signed]	Date7.	-6-73	, 19		
Number of sacks of cement used in well seal12 sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.					
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		<i>-</i>			
Brand name of bentonite	Water Well Contractor's Certification:					
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdi	iction an	d this r	report is		
f waterlbs./100 gals.	true to the best of my knowledge and belief.					
Was a drive shoe used? 꽃 Yes □ No Plugs Size: location ft. Did any strata contain unusable water? □ Yes ☒ No	Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)					
Type of water? depth of strata	Address 7641_35th Ave. NE_Salem, Oregon					
Method of sealing strata off	6) \ () \ () \ \ \ \ \ \ \ \ \ \ \ \ \ \	1	J D			
Was well gravel packed? ☐ Yes ② No Size of gravel:	[Signed] (Water Well Contr	actor)	<u>/</u>			
	Contractor's License No2 Date .7-	•		10		
Fravel placed from ft. to ft.	Date ./			, LÖ		