NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

## JUL 2 3 19 FATE OF OREGON G-38/3 G 328c

State Well No. 6/2w-5 F/

filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

of well completion. STATE ENGINEER	G3280 State Ferrit No.	***************************************	
(1) OWNER: SALEM OREGON	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Oak Crest Farm	Was a pump test made? X Yes 🗌 No If yes, by whom	? Stet	tler
Address 2770 Wallace Rd NW	Yield: 600 gal./min. with 29 ft. drawdov	vn after 2	2g hrs.
Salem, Ore,	<u>" 500 " 22 "</u>	]	. "
(2) LOCATION OF WELL:	2) 2) 17		"
· ·	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Marion Driller's well number 6/2W-5F	Artesian flow g.p.m. Date		
1/4 1/4 Section T. R. W.M.	Temperature of water Was a chemical analysis i	made? 🔲 እ	Zes □ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below co	1	12
	(12) WELL LUG: Diameter of well below of	asing	
	Depth drilled 221 ft. Depth of completed w	ell 22]	L ft.
	Formation: Describe by color, character, size of materic show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c	il and structhe materi hange of j	cture, and lal in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):		111011	10
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Top soil	<del>  0</del>	1
Hew Wen in Beepening in Inconductioning in Item 12.	Yellow clay	11	15_
addition, describe material and procedure in rich iz.	Yellow silty clay	15	35_
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue silty clay	35	70_
Domestic   Industrial   Municipal   Rotary   Driven	_ Muddy blk sand	70	83_
Cable 🚰 Jetted 🗌	Clean coarse sand	83	93
Irrigation X Test Well  Other Dug Bored	Olean sand & gravel	93	105
(6) CASING INSTALLED: Threaded □ Welded \( \bar{\bar{\Bar}} \)	Muddyablk sand	105	115
12 3/4Diam. from 1\(\frac{1}{2}\)O ft. to 221 ft. Gage250	Sand & gravel	1115	123
"Diam, from ft. to ft. Gage	Clean brwn sand & gravel	123	143
	Gravel with clay	1/13	1/15
"Diam, fromft. Gage	Sticky blue clay	1/15	157
(7) PERFORATIONS: Perforated? ★ Yes □ No	Clean blk sand	157	168
Type of perforator used Mills	Blue sticky clay	168	184
Size of perforations 5/16 in. by 21 in.	Fine blk sand with rotted		**************************************
180 perforations from 1211 ft. to 144 ft.	vegetation vegetation	184	186
528 perforations from 1975 ft. to 219 ft.	Clean blk sand with few		100
perforations fromft. toft.		186	193
perforations fromft. toft.	gravels		
	Sand & gravel	193	200
perforations fromft. toft.	_ Muddy sand	200	201
(8) SCREENS: Well screen installed? ☐ Yes 🖺 No	Clean sand	201	203
Manufacturer's Name	Clean sand & gravel	203	221_
Type Model No.		ļ	· · ·
Slot size Set from ft. to ft.	6 106 107	1- 16	<u> </u>
Diam, Slot size Set from ft. to ft.	Work started $6/26/65$ 19 . Completed 7	/13/6	5 19
	Date well drilling machine moved off of well		19
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Bentonite			
Depth of seal 18 ft. Was a packer used? no	Manufacturer's Name		*********
Diameter of well bore to bottom of seal 16 in.	Type: H.P.		
Were any loose strata cemented off? ☐ Yes ∑ No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ⚠ Yes ☐ No	Per 1		
***	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? ☐ Yes № Size of gravel:			
Gravel placed fromft. foft.	NAME Harry A. Robinson		
Did any strata contain unusuable water?   Yes   No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 2214 Front St. NE Salem, Ore.		
Method of sealing strata off	_		
(10) WATER LEVELS:	Drilling Machine Operator's License No. 63		
Static level 33 ft. below land surface Date 7/13/6			
Artesian pressure lbs, per square inch Date	Contractor's License No. 22 Date 7/2	22/65	19
(USE ADDITIONAL SH	EETS IF NECESSARY)		.,