NOTICE TO WATER WELL CONTRACTOR The original and first copy of this room are to be filed with the water well report water well report water resources department.

SALEM, OREGON 97310

within 30 days from the date

STATE OF OREGON

(Please type or print)

within 30 days from the date of well completion. WATER RESOURCES DEFFILE a	bove this line) State Permit I	Vo
(1) OWNER:	(10) I OCATION OF WITH	
• •	(10) LOCATION OF WELL:	
Name Eldreidge School Dist. c/o Lawrence H. Hit Address 7042 Portland Rd. NE	1 E	
Salem Oregon 97303	-42	R. 2W W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner
		ر د و خو د ه قد را تمرین د د د د د د د د د د د د د د د د د د د
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed w	zell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55	
Rotary Driven Domestic N Industrial Municipal Domestic N Industrial Municipal Domestic N		
Dug □ Bored □ Irrigation □ Test Well □ Other □		
CASING INSTALLED: Thresded Welded W	(10) ******* * 0.0	
6 "Diam from top ft. to 109 ft. Gage 250	Depth drilled 109 ft. Depth of completed well 109 ft.	
Diam. from	Formation: Describe color, texture, grain size	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratu	m and acuifor nonotrated
PERFORATIONS: Perforated? Yes X No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion Report such above to
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Topedil	0 2
perforations fromft. toft.	Brown Clay	2 53
perforations from ft. to ft.	Blue Clay	53 55
perforations from ft. to ft.	Black Sand	55 86
(7) SCREENS: Well screen installed? [] Ver [VNc.	Black Sand and Gravel	86 90
Water Manager Tea Wild	Blue Clay	90 94
Manufacturer's Name	Brown Clay	94 99
Type	Slightly Cemented Brown sand	
Diam. Slot size Set from ft. to ft.	and Gravel	99 XXX
Diam. Slot size Set from ft. to ft.		109
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? X Yes \(\subseteq \text{No If yes, by whom? driller} \)		
Yield: 60 gal./min. with 34 ft. drawdown after 5 hrs.		
" " "	**	
Airtest 75 GPM for a period of 1, hour "		
Bailer test gal./min. with ft. drawdown after hrs.		
in s.	A CONTRACTOR AND A CONT	
	Z- <u>-</u>	
berature of water Depth artesian flow encountered ft.	Work started 5/19/79 19 Complete	a 5/19/79 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5/19/79 19
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my	direct cunonvioles
Diameter of well bore to bottom of seal 10 in.		above are true to my
Diameter of well bore below seal	best knowledge and benef.	4
Number of sacks of cement used in well seal 11 sacks	[Signed] (Drilling Machine Operator)	Date 5/21/79 ₁₉
How was cement grout placed? pumped in thru conductor	Drilling Machine Operator's License No	752
pipe	- Land	
	Water Well Contractor's Certification:	
The state of the s	This well was drilled under my jurisdiction and the	
Was a drive shoe used? X Yes I No Rugs Size: location ff.	true to the best of my knowledge and belief.	
Did any strata contain unusable water 🔲 Yes 🐰 No	Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 7365 O'Neill Rd. NE Sale	(Type or print)
Method of sealing strata off	A A A	m, Uregon 9/303
Was well gravel packed? ☐ Yes XNo - Aze of gravel:	[Signed] Dallas & Dans	
	(Water Well Contrac	
Gravel placed from ft. to ft.	Contractor's License No. 561 Date	5/21/79 19