NOTICE TO WATER WELL CONTRACTOR

of well completion.

The original and first copy of this report are to be filed with the WATER RESOURCES DEPARAMENT. CEVE ATE OF OREGON SALEM, OREGON 97310 within 30 days from the date of well completion.

APR 4 1070 (Paret WILL REPORT State V. Please type or print)

APR 4 1979 (Do not write above this line)

	<i>(</i>	05/2	ur C
State Wel	1 No. 🐪	2919	<u> </u>

State Permit	No.	***************************************

(1) OWNER: SALEM OFFT.				
VALUM, EINECOM	(10) LOCATION OF WELL:			
Name Eric Cerneliussen	County Marian Driller's well number 78-17			
Address 10703 River Rd. N.E.	% Section 6 T. 6S	R. 2W	W.M.	
Gervais, Oregen 97026	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well 🐧 Deepening 🗌 Reconditioning 🖂 Abandon 🗀				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	46	ft.	
Rotary Driven Domestic Industrial Municipal	Static level 20 ft. below land s			
Cable	Artesian pressure lbs. per squar			
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well h			
8 "Diam. from +1 ft. to 101 ft. Gage .250	Junicoci of well k	_		
ft. Gage	Depth drilled 101 ft. Depth of comple		101 ft.	
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratus	m and aguif	fer penetrated.	
PERFORATIONS: Perforated? **I Ves. □ No.	with at least one entry for each change of formal position of Static Water Level and indicate prin	tion. Report	each change in	
Type of perforator used terch		 	dearing strata.	
	MATERIAL	From	To SWL	
Size of perforations 2 in. by 4 in. 40 perforations from 96 ft. to 101 ft.	Tep Seil	0	2	
Deliotations Tri	Brewn Clay	1 1	20	
perforations fromft. toft. perforations fromft. toft.	Brewn Clay & Sand Blue Clay		23 44	
	Blue Clay & Black Sand		46	
(7) SCREENS: Well screen installed? Yes No	Black Sand (Heaving)		58 20	
Manufacturer's Name	Blue Grey Clay & Sand		65	
Type Model No.	Brewn Sand & Gravel	65 1	01 20	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.		ļ		
Jeth Stot Size Set Holl				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☑ Yes ☐ No If yes, by whom?		 		
Yield: 130 gal./min. with 30 ft. drawdown after 4 hrs.				
" " "				
n " " " " " " " " " " " " " " " " " " "				
Bailer test gal./min. with ft. drawdown after hrs.	43 5			
	·			
perature of water 52 Depth artesian flow encountered	11 12			
<u></u>	Work started 11-13- 19 78 Complete Date well drilling machine moved off of well		-30 19 78	
(9) CONSTRUCTION:			<u>-28 1979</u>	
4 0	Drilling Machine Operator's Certification: This well was constructed under my	dinast		
Well sealed from land surface toft. Diameter of well bore to bottom of seal 10in.	Materials used and information reported	above are	true to my	
Diameter of well bore below seal	pest knowledge and belief.			
Number of sacks of cement used in well sealsacks	[Signed] Thomas D Flow] (Drilling Machine Operator)	Date3	31, 19.7.9.	
How was cement grout placed?	Drilling Machine Operator's License No	978		
gravity fed from tep	Water Well Contractor's Certification:			
	This well was drilled under my jurisdic	ction and ti	his report is	
Was a drive shoe used? X Yes \(\subseteq No Plus \) No Eige: location ft.	true to the best of my knowledge and beli-	ef.	g v 20	
Did any strata contain unusable water? [Yes] No	Name FLORES WELL DRILLING (Person, firm or corporation)	(Type o	r nrint)	
Type of water? depth of strata	Address 12143 River Rd. N.E.			
Method of sealing strata off		-y		
Was well gravel packed? [] Yes W No Size of gravel:	[Signed] (Water Well Contra	ictor)	****************	
Gravel placed from ft. ft.	Contractor's License No590 Date	331	10 70	
	EETS IF NECESSARY)			