

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

3814 MARI...

WATER WELL REPORT RECEIVED

STATE OF OREGON (Please type or print)

JUN 8 1976

State Well No. State Permit No.

(Do not write above this line) WATER RESOURCES DEPT.

SALEM, OREGON

(1) OWNER:

Name Robert Zielinski Sr. Address Rt. 1 Box 59 Gervais OR 97026

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [x] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from top ft. to 140 ft. Gage 250

(6) PERFORATIONS:

Type of perforator used Mills Knife Size of perforations 7/16 in. by 2 3/4 in. 670 perforations from 66 ft. to 117 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? driller Yield: 250 gal./min. with 5 ft. drawdown after 1 hrs. 400 " 15 " 1 " 600 " 23 " 3 " Baller test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal-Material used Portland Cement Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 14 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal 20 sacks Number of sacks of bentonite used in well seal Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [x] Yes [] No Size: location Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 1953 1/4 Section 6 T. 6S R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 61 ft. Static level 11 ft. below land surface. Date 5/20/76 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10 Depth drilled 150 ft. Depth of completed well 140 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Brown Topsoil, Brown Silty Clay, Blue Silty Clay, Black Sand And Gravel, Brown cemented Sand And Gravel, Gray silty Clay.

Work started 5/14/76 19 Completed 5/20/76 19 Date well drilling machine moved off of well 5/21/76 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Dallas J. Beech Date 5/21/76, 19 Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Willamette Drilling Co. (Person, firm or corporation) (Type or print) Address 1450 Barnick Rd. NE Salem, Oregon 97303 [Signed] Dallas J. Beech (Water Well Contractor) Contractor's License No. 561 Date 5/21/76, 19