NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORTS OF STREET OF OREGON AND STREET OF STR

STATE	ENGINEER, SALEM, OREGO
~	ENGINEER, SALEM, OREGO within 30 days from the date
	of well completion

Apr. G-3040

6/2W-\$ 7A

State Permit No. 6-2836

(1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name W.S. BOAZ SALEM OREGON	Was a pump test made?▼ Yes ☐ No If yes, by whom? DRILLER
Address RT. I BOX 37	Yield: 410 gal./min. with 137 ft. drawdown after 4 hrs.
BROOKS, OREGON	<u>" 330 " 106 " 4 "</u>
(2) LOCATION OF WELL:	<u> </u>
County MARION Driller's well number 997	Bailer test gal./min. with ft. drawdown after hrs.
4 CC - OIT	Artesian flow g.p.m. Date
	Temperature of water Was a chemical analysis made? Yes No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled I40 ft. Depth of completed well I40 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(3) TYPE OF WORK (check):	TOP SOIL FROM TO TO
· · · · · · · · · · · · · · · · · · ·	
New Well Deepening Reconditioning Abandon and and and procedure in Item 12.	
and officers, describe material and procedure in 100m 22.	SAND 30 35
(4) PROPOSED USE (check): (5) TYPE OF WELL:	CLAY 35 55
Domestic □ Industrial □ Municipal □ Rotary □ Driven □	SAND 55 65 CLAY 65 75
Irrigation X Test Well Other Dur Bered	
Dug Bored	SAND 75 95 CLAY 95 IOO
(6) CASING INSTALLED: Threaded Welded X	GRAVEL JOO 140
IO Diam. from TOP ft. to I40 ft. Gage 250	GUAVEL 100 140
ft. Gage	
" Diam. fromft. Gage	
(7) PERFORATIONS: Perforated? Ves No	
Type of perforator used MCLLS	
Size of perforations 2 in. by 3/8 in.	
perforations from ft. to ft.	
480 perforations from IO2 ft. to I39 ft.	
perforations fromft. toft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes 👿 No	
<u>.</u>	
Manufacturer's Name Model No	
Slot size Set from ft. to ft.	Work started JAN. I 1965 . Completed JAN. 16 1965
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well JAN. I6 1965
(9) CONSTRUCTION:	(13) PUMP:
under Apper"	(15) 1 0.111.
Well seal-Material used in seal CEMENT & PUDDLE CLAY	Manufacturer's Name
Depth of seal .20 ft. Was a packer used?	Type: H.P.
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:
Were any loose strata cemented off? Tyes I No Depth	
Was a drive shoe used? XYes INO Size of gravel:	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
The state of the s	
Gravel placed from ft. to ft.	NAME WILLAMETITE DRILLING CO (Person, firm or corporation) (Type or print)
Did any strata contain unusuable water?	Address RT. 2 BOX 276 SALEM, OREGON
Type of water? depth d strata	AAMA GOO
Method of sealing strata off	Drilling Machine Operator's License No. 179
(10) WATER LEVELS:	6 1000
Static level 25 ft. below land surface Date I/16/65	[Signed] (Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date JAN 16 1965
	HEETS IF NECESSARY)