NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 9730 within 30 days from the date of well completion.

RECEIVED
STATE OF OREGON OCT 1 1974 State Well No. 65 2W-9

(Pl	ease ty	pe or	print	STATE	ENGINEER	State	Permit	No.		
(Do not	write	above	this	"5% LEM	, OREGON				,	<i>I</i>

card in oxx 14	1					
(1) OWNER:	(10) LOCATION OF WELL:					
Name An astas Sharabarin	County Marion Driller's well number					
Salem Ore 97305	14 Section 9 T. 69					
	Bearing and distance from section or subdivisio	n corner				
(2) TYPE OF WORK (check):	About & Distanc from	<u> </u>				
New Well Deepening Reconditioning Abandon	To Boar of Place					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	.11				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	Z ft.				
Rotary Driven Domestic Industrial Municipal D						
Cable Jetted Domestic Industrial Municipal	Static level 6 ft. below land su					
Doted Intigation Fresh went Other	Artesian pressure lbs. per square	inch. Date				
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well be	elow casing				
# Diam from O ft. to 110 ft. Gage 250	Depth drilled //U ft. Depth of comple	-				
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size an	142 2 2 2 2				
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum	and aquifer penetrated,				
(b) PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formati position of Static Water Level and indicate princ					
Type of perforator used Star	MATERIAL	From To SWL				
Size of perforations 38 in. by 1/2 in.		 				
350 perforations from 80 ft. to 108 ft.	Beaver Dam	0 3				
	Darke Blue Elay	8 42				
perforations fromft. toft.	sand of longe orani	74 108 6				
(7) SCREENS: Well screen installed? Yes No		108 110 -				
Manufacturer's Name						
Type Model No.						
Diam. Slot size Set from ft. to ft.	- 10 Marie					
Diam. Slot size Set from ft. to ft.						
(8) WELL TESTS: Drawdown is amount water level is lowered below static level						
Was a pump test made? Yes No If yes, by whom?						
eld: gal./min. with ft. drawdown after hrs.	40					
n						
n " " " " " " " " " " " " " " " " " " "						
Bailer test \mathcal{GO} gal./min. with \mathcal{H} ft. drawdown after / hrs.	Simple Control of the					
Artesian flow g.p.m.	7					
	The street of th					
Depth artesian flow encountered ft.	Work started 10 -4 19 7 C/Completed					
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10-9 1974				
Well seal-Material used Cement	Drilling Machine Operator's Certification:					
Well sealed from land surface to ft.	This well was constructed under my (Materials used and information reported a	lirect supervision.				
Diameter of well bore to bottom of sealin,	best knowledge and belief.	bove are true to my				
Diameter of well bore below seal in.	[Signed] to kn W 13ech D	ate 10-9 1971				
Number of sacks of cement used in well seal6sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.	437				
Number of sacks of bentonite used in well salsacks	Drining Machine Operator's License No	Ser-Consular and a series and a				
Brand name of bentonite	Water Well Contractor's Certification:					
Number of pounds of bentonite per 100 mbns	This well was drilled under my jurisdic	tion and this report is				
of water lbs./100 gals. Was a drive shoe used? Yes No_Plugs Size: location ft.	true to the best of my knowledge and belie	f.				
Did any strata contain unusable water? Yes No	Name & W Beck Welldri	11ng				
200	(Person, firm or corporation) Address 2411779 SKylane	Or Conhore,				
Type of water? depth of strata	Address Zaff 1 5 Shylane	r congure,				
Method of sealing strata off	[Signed] toke W Beck					
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contrac					
Gravel placed fromft. toft.	Contractor's License No. 449 Date 10	- 9 <u>184</u>				
(USE ADDITIONAL SH	RETS IF NECESSADV					