NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report FCEIVETR WELL REPORT State Well No. 45/12-9da WATER RESOURCES DEPARTMENT SALEM, ORFGON SEP 1 9 1977 (Please type or print) (Do not write above this line) within 30 days from the date of well completion. OURCES DEPT SALEM. ORECON (10) LOCATION OF WELL: (1) OWNER: Name Union Oil Co. of Calif. Driller's well number D-72-77 County Marion Address 1148 Canal Blvd. Richmond, Calif. % SE % Section 9 T. 4S R. 1W Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Fargo Interchange on Interstate 5 New Well X Deepening [ Reconditioning [ Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🛘 Domestic 🗶 Industrial 🗌 Municipal 🗀 K ft. below land surface. Date 8/14/77 Static level Jetted Cable Dug Bored Irrigation □ Test Well □ Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | X (12) WELL LOG: Diameter of well below casing ...... 16 " Diam from 0 ft to 60 ft Gage • 250 Depth drilled 160 ft. Depth of completed well 12" Diam. from ft. to ft. Gage • 375 Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Tyes M No. Type of perforator used MATERIAL From Size of perforations in. by lay, brown, sandy 0 22 ..... perforations from ...... ft. to ..... ft. 22 Clay, blue, sandy 36 Clay, blue, sticky 36 67 perforations from the fit to the fit. 67 81 Clay, brown ..... perforations from ...... ft. to ...... Sand & Gravel Cemented 81 147 (7) SCREENS: Well screen installed? 🔀 Yes 🛚 No Gravel water bearing 147 155 Manufacturer's Name Johnson Well Screen Type Stainless steel W/bo Clav.blue 155 1.60 Diam. ..... Slot size ..... Set from ..... ..... ft. to ..... Diam. 12" Slot size 30 Set from 145 ft. to 155 ft. Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? X Yes \( \subseteq \) No If yes, by whom? gal./min. with ft. drawdown after hrs. 125 Gal/min 26th 48 hrs \* Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. aperature of water Depth artesian flow encountered ..... ft. 7/15 1977 Completed Work started Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used .. Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Well sealed from land surface to ....... Materials used and information reported above are true to my best knowledge and belief Date 8/11 1977 Diameter of well bore below seal 16 in. (Drilling Machine Number of sacks of cement used in well seal \_\_\_\_\_\_sacks Drilling Machine Operator's Livense No. 883 How was cement grout placed? Cement truck ready mixx Water Well Contractor's Certification: 2½ Yards This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? X Yes | No Plugs ........... Size: location ...... Name S & M Drilling & Supply Inc. (Type or print) Did any strata contain unusable water? 

Yes 399 S. E. Walnut, Canby, Ore. 97013 Type of water? depth of strata

Method of sealing strata off

Gravel placed from ..... ft. to ....

Was well gravel packed? 

Yes 
No Size of gravel: .....

Contractor's License No. 497 Date 8/11, 19.77