

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT MARI... 3926 DEC 18 1967 STATE OF OREGON SALEM OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

(Please type or print) (Do not write above this line)

State Well No. 6/2w-10ddb

State Permit No.

G 5119

(1) OWNER:

Name John Banick Address Rt. 1 Box 157, Brooks, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

12" Diam. from top ft. to 170 ft. Gage 250

PERFORATIONS:

Perforated? [x] Yes [] No.

Type of perforator used Mills Size of perforations 3/4 in. by 2 1/2 in. 300 perforations from 90 ft. to 120 ft. 204 perforations from 150 ft. to 170 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 35 ft. below land surface Date 12/15/67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom? Driller Yield: 300 gal./min. with 4 ft. drawdown after 4 hrs. 500 " 7 " 4 " 700 " 10 " 4 " Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 54 Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal-Material used Cement & Puddle clay Depth of seal 20 ft. Diameter of well bore to bottom of seal 14 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [x] Yes [] No Did any strata contain unusable water? [] Yes [] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1281 1/4 Section 10 T. 6S R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing

Depth drilled 170 ft. Depth of completed well 170 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Yellow Clay, Blue Clay, Brown Sand, Blue clay, Gravel, Sandy blue clay, Gravel.

Work started 11/18/67 19 Completed 12/14/67 19

Date well drilling machine moved off of well 12/15/67 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald W. Norton Date 12/15/67 19 (Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)

Address Rt. 2 Box 276, Salem, Oregon

[Signed] Emil J. Beier (Water Well Contractor)

Contractor's License No. 2 Date 12/14/67 19