NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

State Permit No. G-3404, G-7107

		<u></u>	
(1) OWNER: E.	(11) WELL TESTS: Drawdown is amount vlowered below static le	water leve vel	el is
Name WENDELLE BARNETT	Was a pump test made? Yes No If yes, by whom	1?	
Address RT.I BOX I54	Yield: gal./min. with ft. drawdow	n after	hrs.
BROOKS, OREGON	" "		
(2) LOCATION OF WELL:	Raller test 45 gal /min with 5 st drawdo		
County MARION Driller's well number II52	Ballet test gal./illii, with - it. drawdo	wn after	hrs.
14 14 Section II T. 6 S R. 2 W W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis r	nade? 🔲 🏾	es □ No
	(12) WELL LOG: Diameter of well below car	sing	
	Depth drilled I7I ft. Depth of completed well	17I	ft.
	Formation: Describe by color, character, size of material	l and stru	cture, and
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each of	he materi nange of j	al in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	TOP SOIL	0	3
New Well Deepening □ Reconditioning □ Abandon □	BROWN SILT	3	30
bandonment, describe material and procedure in Item 12.	GRAY SILT	30	40
(A) PROPOSED LISE (about). (E) TWDE OF WELL.	GRAY CLAY WITH SAND	40	90
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAY CLAY	90	100
Cable A Jetted	BLACK SAND & GRAVEL	IOO	
Irrigation Test Well Other Dug Bored	GRAY CLAY & GRAVEL	IIO	126
(6) CASING INSTALLED: Threaded Welded W	BLACK SAND & GRAVEL	I26	130
6	GRAY CLAY	I30	I56
"Diam. from ft. to ft. Gage ft	BLACK SAND	I56	I6 I
"Diam. fromft. toft. Gage	BLACK SAND & GRAVEL	I6I	I7I
(7) PERFORATIONS: Perforated? ☐ Yes No			
Type of perforator used			
Size of perforations in by in.			
ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations fromft. toft.			
(8) SCREENS: Well screen installed? Yes X No			
Manufacturer's Name			
Model No.		<u> </u>	-
n	Work started JUNE 15 1966 Completed JU	NE 27	I966
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well JUNE	27 I9	6619
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal CEMENT & PUDDLE CLAY	Manufacturer's Name		
Depth of seal ft. was a packer used?	Type:		
Diameter of well bore to bottom of seal in.	Wishers Will Control of the Control		
Were any loose strata cemented off? Tes I No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? Xes No	This well was drilled under my jurisdiction a	nd this	report is
Was well gravel packed? Yes 1 No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed fromfttoft.	NAME WILLAMETTE DRILLING CO		
Did any strata contain unusable water? 🔲 Yes 🗍 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON		
Method of sealing strata off	Drilling Machine Operators I to	T	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 151		
- -	[Signed] Emil O. Beiler		
Static level 45 ft. below land surface Date 6/27/66	(Water Well Contractor)	A ===	•
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date JUNE	27 I9	б Б

(USE ADDITIONAL SHEETS IF NECESSARY)