NOTICE TO WATER WELL CONTRACTOR ARI filed with the

STATE ENGINEER, SALEM, OREGON 3300 1 3 1965

STATE OF OREGON (Please type or print) State Well No. 6/2w-12N LWATER WELL REPORT State Permit No. Drawdown is amount water level is lowered below static level (1) OWNER: TOM PRATEM OFFICEN (11) WELL TESTS: Name Was a pump test_made? XYes \(\subseteq \text{No If yes, by whom? } \) DR ILLER RT.I BOX 143 BROOKS.OREGON gal./min. with 68 ft. drawdown after Yield: 600 Address IO hrs 550 60 IO 500 55 IO " (2) LOCATION OF WELL: MAKAKA 400 gal./min. with 42 ft. drawdown after IO hrs **I077** MARION Driller's well number g.p.m. Date Artesian flow 2 W II T.6 S Temperature of water Was a chemical analysis made? ☐ Yes ☐ No Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing . Depth drilled 170 ft. Depth of completed well Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL MOST (3) TYPE OF WORK (check): TOP SOIL 3 Well 🔟 Deepening [Reconditioning [Abandon □ BROWN CLAY 40 andonment, describe material and procedure in Item 12. BROWN SAND &XXMALKXCRAYEL 40 44 @RAYx@LAYxxxxxxxxxxxxxxxxxxxxxx (4) PROPOSED USE (check): (5) TYPE OF WELL: BROWN SAND & SMALL GRAVEL 80 Rotary | Driven | Domestic | Industrial | Municipal GRAY CLAY 80 **I05** Jetted [7] Irrigation Test Well | Other Dug Bored [BLACK SAND **I05 I20** GRAY CLAY (6) CASING INSTALLED: **I20 I35** Threaded [] Welded BLACK SAND **I35** IO Diam from TOP ft. to T70 ft. Gage 250 BLACK SAND & GRAVEL ." Diam. from ft. to ft. Gage (7) PERFORATIONS: Perforated? Yes No Type of perforator used in. by Size of perforations 380 perforations from ____ perforations from ... ft. to perforations from .. perforations from _____ ft. to ____ (8) SCREENS: Well screen installed? 🗌 Yes 🛣 No Manufacturer's Name n. Slot size Set from -Work started AUG. 16 1965 Completed AUG . 27 186 Diam. Slot size Set from Date well drilling machine moved off of well AUG. 2 (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal CEMENT & PUTTLE CLAY Manufacturer's Name Depth of seal 20 ft. Was a packer used? Diameter of well bore to bottom of seal in. Water Well Contractor's Certification: Were any loose strata cemented off?

Yes

No Depth This well was drilled under my jurisdiction and this report is Was a drive shoe used? XYes No ___ true to the best of my knowledge and belief. Was well gravel packed?
Yes NAME WILLAMETTE DRILLING CO. Gravel placed from Did any strata contain unusable water? Yes 🔲 No RT.2 BOX 276 SALEM, OREGON Type of water? Method of sealing strata off (10) WATER LEVELS: ft. below land surface Date 8/27/65 Static level Contractor's License No. 2 Date AUG.27 Ibs per square inch Date Artesian pressure

(USE ADDITIONAL SHEETS IF NECESSARY)