JAN 20 1959

MAX 39 88 WATER WELL REPORT

State Well No. G-1246

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE OF OREGON

(1) OWNER: Anton Pfau Jr.	(11) WELL To	ade? 🔏 Yes	Drawdown is amou lowered below stati	thom? Dri.	Ller
Address 4460 Labish Garden Road	Yield: 215	gal./min. wit	hNone ft. draw	down after 3	hrs.
Salem, Oregon	,,	,,	1	19	ਾ ਮ ਦਾਉਸਤਾ ਦ ਾਂਟ
(a) TO GALLYON, OF THE I	***	**			
(2) LOCATION OF WELL:	Bailer test	gal./min. wit	h ft. draw	down after	hrs.
County Marion Owner's number, if any—	Artesian flow 3		g.p.m. Date		
14 14 Section T. R. W.M.	Temperature of wa	ter 57 was	a chemical analysi	s made? 🗌 Ye	s □% o
Bearing and distance from section or subdivision corner	710) XXVEX X X	OC.	Diameter of wel	, 10	inches.
G-1246	(12) WELL L	0	Depth of complete	100	ft.
550's & 495' West From	Depth drilled	he her solon, ol	haracter size of ma	terial and struc	ture, and
510 3 4 712 NOT 37017	Formation: Descri show thickness of stratum penetrated	aquifers and t	he kind and nature	of the materio	l in each
The second secon	stratum penetratea	MATERIAI		FROM	TO
	m			111012	
(3) TYPE OF WORK (check):			eaverdam)	2	<u>2</u> 5
New Well Deepening Reconditioning Abandon			& Wood		
If abandonment, describe material and procedure in Item 11.	Blue C1		**	5	<u>36</u>
A) PROPOSED USE (check): (5) TYPE OF WELL:	Brown C			36	51
(1) 1110101011	Brown S	andy Cl	ay	51	90
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ Cable ※☐ Jetted ☐	Brown S	and & C	<u>ravel</u>	90	100
Irrigation T Test Well Other Dug Bored					
<u> </u>					
(6) CASING INSTALLED: Threaded □ Welded □ X					
TABX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX					
10 " Diam. from Top ft. to 100 ft. Gage 31.20#		4			
"Diam. fromft. toft. Gage					
47					
(7) PERFORATIONS: Perforated?					
Type of perforation used size of perforations in. by in.					
SIZE of perforations in. by in. perforations from ft. to ft.					
perforations from ft. to ft.		477 - 477 - 1			
perforations fromft. toft.					
perforations from					
perforations fromft. toft.					
perforations fromft. toft. perforations fromft. toft.	, , , , , , , , , , , , , , , , , , , ,				
(6) Bellinging	771				
Manufacturer's Name Model No.		<u> </u>			
Lype			The second secon		
II. manning Side Bibb manning to the state of the state o	Work started 9.	-29-59	19 . Completed	12-11	-58,
Slot sizeSet fromft. toft.	WOLK Started		. Compressed		
(9) CONSTRUCTION:	(13) PUMP:		•		
Was well gravel packed? Yes No Size of gravel:	Manufacturer's N	ame	**************************	. , ,	~******
Gravel placed fromft toft.	Туре:	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	*************************************	H.P	*************
Was a surface seal provided? Yes \(\times \text{No} \) To what depth? \(\text{LO} \) ft.					
Material used in seal— Drill cuttings	Well Driller's S	tatement:			
Did any strata contain unusable water Yes No			der my jurisdict	ion and this	report is
Type of water? Depth of strata	true to the best	of my know	ledge and belief.		
Method of sealing strata off	NAME	Orvill	e Wymore	(Type or prin	
(10) WATER LEVELS: Flow 35 G.P.M.	(Person, firm, or corporation) (Type or print) Address Rt.1 Brooks Oregon				
Flows et below land surface Date 12-11-08	•				
Artesian pressure lbs. per quare inch Date	Driller's well nu	umber	<u> 458</u> .		
Log Accepted by	[Signed]	ulle U	(Well Driller)	**************************************	~~
[Signed] auto Harmate Jan 9, 1937	License No	88	Date 12	<u>1.7</u>	, 19
(Owner) / / (/	•			THE MAN THE TY SALE	