

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from date of well completion

RECEIVED MAR 4.002 WATER WELL REPORT JUN 2 1969 STATE OF OREGON SALEM OREGON

State Well No. G/ZW-14 dbd State Permit No. G-4943

(1) OWNER:

Name Max Mo Bibby Address 6826 Labish Center Road NE Salem, Ore.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from top ft. to 160 ft. Gage 250

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used Mills Size of perforations 2 in. by 3/8 in. 330 perforations from 70 ft. to 95 ft. 280 perforations from 100 ft. to 132 ft. 310 perforations from 136 ft. to 159 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to

(8) WATER LEVEL: Completed well.

Static level 1 ft. below land surface Date 5-28-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Driller 300 gal./min. with 35 ft. drawdown after 3 hrs. 400 " " 45 " " 3 " 500 " " 56 " " 3 " 600 gal./min. with 70 ft. drawdown after 3 hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal-Material used Drill cuttings, Puddle Clay Depth of seal 20 ft. Diameter of well bore to bottom of seal in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [x] Yes [] No Did any strata contain unusable water? [] Yes [] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1399 1/4 Section 14 T. 6 R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing Depth drilled 160 ft. Depth of completed well 160 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Gray Clay, Blue Clay, Black Sand, Cemented Gravel, Blue clay, Cemented gravel, Blue clay, Loose gravel, Cemented gravel.

Work started 5-10-69 19 Completed 5-28-69 19 Date well drilling machine moved off of well 5-28-69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Donald Norton Date 5-29-69, 19. (Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE Salem, Oregon 97303

[Signed] Emil D. Beier (Water Well Contractor)

Contractor's License No. 2 Date 5-29-69, 19.