NOTICE-TO WATER WELL CONTRACTOR	ARX 4005)		· 0.
The original and first copy of this report are to be filed with the	F OREGON State Well No. pe or print)	. 1	14 \$
filed with the 1067SFATE O	F OREGON State Well No.	6/24	
state engineer, salem, oregon 97310 2 3 1967SFATE of the within 30 days from the date	pe or print) G-1964	,	
	pe or print) above this line)  G-4363	۲o	
	7		
(1) OWNER:	(11) LOCATION OF WELL:		
Name Mrs. Ruth Harris	County Marion Driller's well number 1254		
Address Rt. 1 Brooks, Oregon	34 34 Section 13&124 6 R. 2W W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well Deepening Reconditioning Abandon	•	<del></del>	
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):			******
Rotary Driven Demostic Demostic Deficient	(12) WELL LOG: Diameter of well	_	
Cable X Jetted   Domestic   Industrial   Municipal   Dug   Bored   Irrigation X Test Well   Other	Depth drilled 135 ft. Depth of comp	leted well ]	35 ft
CASING INSTALLED: Threaded   Welded	Formation: Describe color, texture, grain size and show thickness and nature of each strat	and structure	of materials
	with at least one entry for each change of form	nation. Repor	t each change
10" Diam. from top ft. to 135 ft. Gage 250	in position of Static Water Level as drilling pr	oceeds. Note	drilling rates.
"Diam. from	MATERIAL	From	To SWL
	Top soil	0	2
PERFORATIONS: Perforated? T Yes   No.	Yellow clay		<u>o</u> —
Type of perforator used Mills	Brown sandy silt		9 74
Size of perforations 2 in. by 3/8 in.	Black sand & gravel		5 14
300 perforations from 100 ft. to 135 ft.	Gray clay Black sand		7 4
50 perforations from 40 ft. to 45 ft.	Brown sand & small grave		8
perforations from ft. to ft.	Black sand & gravel	98 12	
perforations fromft. toft.	Brown sand & gravel	123 13	
perforations from ft. to ft.			
(7) SCREENS: Well screen installed?   Yes X No			
Manufacturer's Name			
Type Model No.	<u> </u>		
Diam. Slot size Set from ft. to ft.		<del> </del>	
Diam. Slot size Set from ft. to ft.	2		
(8) WATER LEVEL: Completed well.			
Static level 13 ft. below land surface Date			
lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level		ļ	
_ = 1 N			
Was a pump test made? I Yes No If yes, by whom? Driller	Work started 8/4/67 19 Complete	ed8/24/6	77 10
Yield: '500 gal./min. with 55 ft. drawdown after 8 hrs.	Date well drilling machine moved off of well		
		724/07	19
" " " "	Drilling Machine Operator's Certification:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my d rials used and information reported about	rect supervi ve are true	sion. Mate- to my best
Artesian flow g.p.m. Date	knowledge and belief.		-
Temperature of water 53 Was a chemici analysis made? ☐ Yes ▼ No	[Signed] Kenneth Mosque de (Orilling Machine Operator)	Date 8/25	/6.7 19
(10) CONSTRUCTION:		_	
Well seal-Material used Cement Puddle clay	Drilling Machine Operator's License No. 474		
Depth of sealft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of set 14 in.	This well was drilled under my jurisdiction and this report i-		
Were any loose strata cemented off? Yes X No Depth	true to the best of my knowledge and belief.		
Was a drive shoe used? TYes 🔲 No	NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water	Address Rt. 2 Box 276, Salem, Oregon		
Type of water? depth of strata	O D D D DOLEMA VIESON		
Method of sealing strata off	[Signed] Cmil O Besac		
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor)		
Gravel placed fromft. toft.	Contractor's License No. 2 Date 8/	25/67	, 19
(USE ADDITIONAL SH	EETS IF NECESSARY)	_	