NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WEI	LL REPORT OREGON G-5795 State Well No.	6/2w-1	ee 4 N-
STATE OF STATE OF STATE OF Within 30 days from the date. of well completion. APP 8 1968	e or print) bove this line) $G - \frac{4811}{6 - 4324}$ State Permit No) <u>.</u>	,
(1) OWNER:	(11) LOCATION OF WELL:		
Name H. D. Coom JER	County MARION Driller's well number		
Address 6796 - 62 nd duling			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing		
Cable Jetted Domestic Industrial Municipal	Depth drilled & ft. Depth of comple	eted well	Ø ft.
Dug Bored Irrigation Test Well Other	Formation: Describe color, texture, grain size a	and structure of n	naterials;
ASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum and aquifer penetrated,		
10 " Diam. from 11 tt. to 60 tt. Gage 250	with at least one entry for each change of forms in position of Static Water Level as drilling pro	ation, Report each	n change
" Diam. fromft, toft, Gage	MATERIAL	From To	SWL
"Diam, from ft, to ft. Gage	2/18 0 -1	71011	
DAME LOTE STANDARD OF THE STAN	BLACK - SOIL	0 80	
PERFORATIONS: Perforated? Yes No.	BROWN - CLAY	8 25	
Type of perforator used	13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	25 34	
Size of perforations in. by in.	Spun 2) + Mars D. (SKALE)	37 60	
nerforations from the to the fit.	BI T - CIM	11 (77)	
perforations from 5 tt. to 5 tt.	BACE CAY	63 60	 _
perforations from ft. to ft.	Bernel Laur	12 80	
perforations from ft. to ft.	- CRAFIZE TEMNO	 	
perforations fromft. toft.			
			
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WATER LEVEL: Completed well.			
Static level ft. below land surface Date 3-22-C			
Ar an pressure lbs. per square inch Date	,		
			-
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	ļ		
Was a pump test made? Yes \(\) No If yes, by whom? \(\frac{1}{2} ROBINSCOTT			
Yield: 350 gal./min. with 22 ft. drawdown after 2 hrs.	Work started 3 - 19 - 6 of 19 Complete	<u>ed </u>	19 68
425 " 29 " 3,4	Date well drilling machine moved off of well	<u> </u>	<u> 19 4</u> 8
300 90	Drilling Machine Operator's Certification:	•	
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di		
	rials used and information reported above knowledge and belief.	e are true to r	ny best
Artesian flow g.p.m. Date		11 8-72	10
Temperature of water Was a chemical analysis made? Yes No	[Signed] Moranda Town of (Drilling Machine Operator)	Sate 3-23	., 19.G.J
(10) CONSTRUCTION:	Duilling Moshins Onesstade Lieuws No. 525		
Well seal-Material used SEN Mist 1/18	Drilling Machine Operator's License No. 522		
Depth of seal 30 ft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is		
Were any loose strata cemented off? Yes Ano Depth	true to the hest of my knowledge and belief.		
Was a drive shoe used? ☐ Yes □ No	NAME (Person, firm of corporation) (Type or print)		
Did any strata contain unusable water Yes No	Address 5545 W.C.E. N. ST. C. E.		
Type of water? depth of strata	Address SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS		
	II DO OD SALVEN		
Method of sealing strata off	[Signed] Hanking (Water Well Contractor)		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:			10
Gravel placed fromft_toft.	Contractor's License No. 3.2. Date 3		1940
(USE ADDITIONAL SE	HEETS IF NECESSARY)		