MARI.

NOTICE TO WATER WELL CONTRACTOR TO The original and first copy of this report are to be JUL 10 1964WATER WELL REPORT filed with the STATE ENGINEER, SALEM, OREGON 97810 within 30 days from the date TATE EF GINEE Freeze type or print) G-2 of well completion. G-2940

State Well No. . State Permit No. G.

*

i'm s

CAL DES GALLON	(11) WELL TESTS: Drawdown is amoun lowered below static	t water level	l is
(1) OWNER: RUTH HARRIS	201,0204 11011		TER:
	Was a pump test made? XYes \(\bar{\text{No}}\) No \(\text{If yes, by who}\) Yield: \(\bar{500}\) gal./min. with \(\bar{20}\) ft. drawd	own after	hrs.
Address RT.I BROOKS, OREGON	" 370 " 16 "	DWII CILCOL .	4 "
	" 330 " 1 5 "		1 "
(2) LOCATION OF WELL:	EXEKE 270 gal./min. with 13 ft. draw	down after	hrs.
County MARION Driller's well number 930	Artesian flow g.p.m. Date		
14 14 Section I5 T. 6 S R. 2 W W.M.	Temperature of water Was a chemical analysi	s made? 🔲 🛚	Yes □ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below	casing	
	` ´	T04	n .
	Depth drilled IOO ft. Depth of completed	11011	
The state of the s	Formation: Describe by color, character, size of mate show thickness of aquifiers and the kind and nature stratum penetrated, with at least one entry for each	of the mater change of	ial in each formation.
Section of the sectio	strutum penetratea, with as teast the single	1	
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL	0	25
New Well Deepening Reconditioning Abandon	SAND	25_	35
andonment, describe material and procedure in Item 12.	CLAY	35	60
PROPOSED USE (check): (5) TYPE OF WELL:	SAND	60	65
Rotary [] Driven []	GRAVEL	65	80
Domestic Industrial Municipal Cable	SAND	80	85
Irrigation Tx Test Well Other Dug Bored	_GRAVEL	85_	IOO
(6) CASING INSTALLED: Threaded Welded X			+
" Diam. fromft. toft, Gage			
8 "Diam. from TOP ft. to IOO ft. Gage 250	The second secon		1
"Diam. fromft. toft. Gage	The state of the s		
(7) PERFORATIONS: Perforated? ★KYes □ No			
Type of perforator used MILLS			<u> </u>
Size of perforations 3/8 in. by 2 2 in.	•		
nerforations from ft. to ft.			
344 perforations from 62 ft. to 98 ft.	· · · · · · · · · · · · · · · · · · ·		
perforations fromft. toft.			
perforations from ft. to ft.		-	1
perforations fromft. toft.			1 .
(8) SCREENS: Well screen installed? Yes Tylo			+
Manufacturer's Name			
TypeModel No.			- *
Slot size Set from ft. to ft.	Work started JUNE 15 1964. Completed	JUNE 2	2 19 6
Diam, Slot size Set from ft. to ft.	Date well drilling machine moved off of well	18	¹⁹ 6
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal CEMENT & PUTTLE CLAY Depth of seal 20 ft. Was a packer used?	Manufacturer's Name	** **	**************
Depth of seal 20 ft. Was a packer used? 10 in.	Type: H.P.		
Diameter of wen bore to bottom of see	Water Well Contractor's Certification:		
Were any loose strata contented ozz.	This well was drilled under my jurisdiction	on and this	renort is
Was a drive shoe used? ▼ Yes □ No □ Size of gravel:	true to the best of my knowledge and belief.	JII CHICA GIIII	, report it
had	NAME WILLAMETTE DRILLING CO	١.	
	(Person, firm or corporation)	(Type or prin	it)
Did any strata contain unusuable water?	Address RT.2 BOX 276 SALEM, OR	EGON	
Type of watery			
	The state of the s	I79	******
Method of sealing strata off	Drilling Machine Operator's License No.		
Method of sealing strata off (10) WATER LEVELS:	Similar Machine Operator's Incense No.	L	
Method of sealing strata off	Similar Machine Operator's Incense No.) or)	***************************************