NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be OCT - 3 193 WATER WELL REPORT filed with the

STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON within 30 days from the date of well completion.

(Please type or print)

State Well No. 6 /2W-16N

State Permit No. .....

(1) OWNER:	original de la companya de la compa La companya de la co	(11) WELL TESTS: Drawdown is amount lowered below static 1	water leve	l is
Name M.C. Nuytten		Was a pump test made? Ty Yes \( \subseteq \) No If yes, by whom		
Address Rt.1 Box 233		Yield: 200 gal./min. with 7 ft. drawdo		ttler
Brooks, Oregon		<u> </u>		7 "
(2) LOCATION OF WELL:		<u> </u>		2 "
County Marion Driller's well number 6/2W-16N		Bailer test gal./min. with ft. drawdd	own after	hrs
14 14 Section T.	R. W.M.	8.00.		<u>St</u>
Bearing and distance from section or subdivis	ion corner	(10) THEFT TOG		
	t	(12) WELL LUG: Diameter of well below c	asing1	0
	( A Company of the Co	Depth drilled 110 ft. Depth of completed w	ell 11	
	A STATE OF THE STA	Formation: Describe by color, character, size of materic show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each continuous control of the control of	l and stru the mater hange of	cture, and ial in each formation
(3) TYPE OF WORK (check):	And the second s	MATERIAL	FROM	TO
	ditioning ☐ Abandon ☐	Top soil	0	2
tandonment, describe material and proce		Yellow clay	2	12
		Yellow silty clay	12	40
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Grey clay	40	55
Domestic 🗌 Industrial 🗎 Municipal 🗌	Rotary Driven Cable No. Jetted	Muddy blk sand Clean blk sand	55	_68_
Irrigation 🕱 Test Well 🗌 Other	Cable 🔼 Jetted 🗌 Dug 🔲 Bored 🗆	Gravel with clay	_68	75
(6) CASING INSTALLED: Three	aded □ Welded 🛣	Clean sand & gravel water	75_	_85_
	<del>-</del>	bearing	0.~	
10 3/4 Diam. from 2/3+0 ft. to 110 ft. Gage . 250 bear "Diam. from ft. to ft. Gage			85	_110_
"Diam. from ft. to ft. Gage				
/FE DIDTOR A MYOLIC				
25 2 3		- Control of the Cont		
Type of perforator used M111s Size of perforations 3/8 in. by	2½ in.	and the same of th		
Size of perforations $3/0$ in. by $2\frac{1}{2}$ in. $400$ perforations from $89$ ft. to $109$ ft.				
perforations fromft.				
perforations from		The state of the s		
perforations from ft. to ft.				
perforations from		The state of the s		
(8) SCREENS: Well screen installed? ☐ Yes ☒ No				
Manufacturer's Name		PAR CALL AND ADDRESS OF THE PARTY OF THE PAR		
TypeN	lodel No.	The state of the s		
Slot size Set from ft. to ft.		0/00/61	16-16-	
Dram. Slot size Set from ft. to ft.		Work started 9/28/61 19 . Completed 10	/6/64	19
(9) CONSTRUCTION:		Date well drilling machine moved off of well 19		
Rent	onita	(13) PUMP:		
Well seal—Material used in seal Bentonite  Depth of seal 18 ft. Was a packer used? no		Manufacturer's Name		L projektora
Diameter of well bore to bottom of sealin.		Type: H.P.		
Were any loose strata cemented off? Yes No Depth		Water Well Contractor's Certification:		
Was a drive shoe used? Yes No				
Was well gravel packed? ☐ Yes ᡯ No S	æ of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	nd this r	eport is
Gravel placed fromft, toft				
Did any strata contain unusuable water? ☐ Yes ☐ No		NAME Harry A. Robinson (Person, firm or corporation) (Type or print)		
Type of water? depth of strata		Address 2214 Front St. NE Salem, Ore.		
Method of sealing strata off		MAMI J. W. A.		
(10) WATER LEVELS:		Drilling Machine Operator's License No. 63		
Static level 24 ft. below land	surface Date 10/5/61	[Signed] Jarry G. Water Well Contractor)		
Artesian pressure lbs. per squa	re inch Date	Contractor's License No. 22 Date 10/	m // 1	
	(USE ADDITIONAL SHI	EETS IF NECESSARY)	··t·\r014···	19