NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 SEP 13 1905 STATE OF OREGON within 30 days from the date STATE ENGINEERs type or print) of well completion.

State Well No. State Permit No. ...

6/26-17

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level lowered below static level	/el is
Vame DON G. VANDOPVORT	Was a pump test made? Yes No If yes, by whom?	
Address RT.I BOX 71 EROOKS, OREGON	Yield: gal./min. with ft. drawdown after	hrs.
	" " " " " " " " " " " " " " " " " " "	
(2) LOCATION OF WELL:	Botter test 40 get /min with 20ft drawdown after	 -
County MARION Driller's well number 1076	Band test - Band min. With Cit. draw down dries	r L hrs.
14 14 Section 17 T. 6 S R. 2 W W.M.	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made?	Ves C No
Bearing and distance from section or subdivision corner	(40) TYPET TOO	
	TOO	
	Depth drilled 100 ft. Depth of completed well 10	
	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mater stratum penetrated, with at least one entry for each change of	rial in each formation.
	MATERIAL FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL 0	2
Well ■ Deepening □ Reconditioning □ Abandon □	YELLOW GLAY 2	3 I
andonment, describe material and procedure in Item 12.	SILTY BROWN SAND 3I	35
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLUE CLAY 35	65
Domestic Industrial Municipal Rotary Driven	BLACK SAND 65	80
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	BLACK SAND & GRAVEL 80	100
(6) CASING INSTALLED: Threaded Welded		
" Diam. from TOP ft. to TOO ft. Gage 250		+
•		†
" Diam, from ft. to ft. Gage		
(7) PERFORATIONS: Perforated? ☐ Yes ■No		
Type of perforator used		ļ
Size of perforations in. by in.		<u> </u>
perforations fromft. toft.		
perforations from ft. to ft.		+
perforations fromft. toft. perforations fromft. toft.		-
perforations from ft. to ft.		
(0) CODERIC.		
Manufacturer's Name		
Model No ft. to ft.	AND TOTAL	
Diam. Slot size Set from ft. to ft.	Work started AUG. 24	19 65
	Date well drilling machine moved off of well AUG. 24	19 65
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in seal CEMENT & PUTTLE CLAY	Manufacturer's Name	
Depth of seal 20 ft. Was a packer used?	Type: H.P.	
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:	
Were any loose strata cemented off? Tyes No Depth		
Was a drive shoe used? Yes \(\bar{\text{No.}} \) No.	This well was drilled under my jurisdiction and this true to the best of my knowledge and belief.	report is
Was well gravel packed? Yes No Size of gravel: Gravel placed from ft.	WITT A MEMORIA TYP TITT THE GO	
Did any strata contain unusable water Ves No	(Person, firm or corporation) (Type or prin	1t)
Type of water? depth of strata	Address RT.2 BOX 276 SALEM, OREGON	••••
Method of sealing strata off	Drilling Washing Orangton's Till 37 807	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 593	
9/24/85	[Signed]	
E 4. D-4.	Contractor's License No. (Water Well Contractor) Date AUG. 24	《 集
Artesian pressure lbs, per square men Date	Date Date	1965