NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED MAR 24 1980 WATER RESOURCES DEPT SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

4188 MAR 1 1980

State Well No. 6s/2w-18 db

State Permit No.

(1) OWNER:
Name BILL SCHMIDT
Address 2090-34th AVE N.E.
SALEM ORE 97303

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from +1 ft. to 100' ft. Gage 5
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 30 gal./min. with 5 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 51 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used QUIK GELL
Well sealed from land surface to 49 ft.
Diameter of well bore to bottom of seal 10" in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal NONE sacks
How was cement grout placed?
QUIK GELL PUMPED AROUND CASING 3½ SACKS
Was a drive shoe used? ☒ Yes ☐ No Plug NO Size: location ft.
Did any strata contain unusable water? ☒ Yes ☐ No
Type of water? SANDY depth of strata 88 TO 91'
Method of sealing strata off CASED
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County MARION Driller's well number
NW ¼ SE ¼ Section 18 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner
WELL AT 8890 HUFF AVE N.E.
SALEM ORE

(11) WATER LEVEL: Completed well.
Depth at which water was first found 88' ft.
Static level 23 ft. below land surface. Date 3-19-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 101' ft. Depth of completed well 101' ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOPSOIL	0	1	
CLAY YELLOW COLOR	1	52	
CLAY SANDY BLUE COLOR	52	68	
SAND BLACK FINE	68	78	
CONGLOMERATE	78	88	
GRAVEL & SAND 1" W.B. WATER IRONY	88	91	
CONGLOMERATE	91	101	
PERMISSION GRANTED BY WATER RESOURCES DEPT TO USE QUIK GELL AROUND CASING	3-10-80		

Work started 3-10 1980 Completed 3-19 1980
Date well drilling machine moved off of well 3-19 1980

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] R.T. Sneed (Drilling Machine Operator) Date 3-19, 1980
Drilling Machine Operator's License No. 187

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name R.T. SNEED WELL DRILLING (Person, firm or corporation) (Type or print)
Address R.T. Sneed 4750 ELIZABETH SALEM ORE
[Signed] R.T. Sneed (Water Well Contractor)
Contractor's License No. 6 Date 3-19, 1980

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119