

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED

WATER WELL REPORT APR 10 1976

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 45/1W-11

WATER RESOURCES DEPT.

SALEM, OREGON

State Permit No.

MARI. 4.19

(1) OWNER:

Name RICHARD JENKS
Address RT 3 BOX 1630
AURORA OREGON 97002

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
10" Diam. from + 1 1/2 ft. to 139 ft. Gage 950
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used MILLS
Size of perforations 1/4 in. by 3 in.
120 perforations from 113 ft. to 123 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? STETLER

Yield: 48 gal./min. with 55 ft. drawdown after 2 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used BENTONITE

Well sealed from land surface to 40 ft.

Diameter of well bore to bottom of seal 16 in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal 5 sacks

Brand name of bentonite NATONAL

Number of pounds of bentonite per 100 gallons

of water 125 lbs./100 gals.

Was a drive shoe used? Yes No Plugs Size: location ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County MARION Driller's well number 2
NW 1/4 SE 1/4 Section 11 T. 4S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft.
Static level 45 ft. below land surface. Date 3-11-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 134 ft. Depth of completed well 134 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	2	
CLAY (BROWN) (HARD)	2	20	
CLAY (BROWN) (SANDY)	20	74	5
CLAY (BLUE)	74	92	
SAND (BLACK) (WB)	92	104	45
CONGLOMERATE (MED)	104	108	45
GRAVEL (MED) (BLACK)	108	114	45
GRAVEL (SMALL) (WB)	114	115	45
CLAY (BLUE)	115	134	

Work started 2-27 19 76 Completed 3-11 19 76

Date well drilling machine moved off of well 3-11 19 76

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] W.A. Pamballa Date 3-11, 19 76
(Drilling Machine Operator)

Drilling Machine Operator's License No. 491

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name BUD'S WELL DRILLING
1287 N. F. CLOVER RIDGE RD. (Type or print)
ALBANY, OREGON 97321

[Signed] W.A. Pamballa
(Water Well Contractor)

Contractor's License No. 621 Date 3-11, 19 76