NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT FOR 17 1968 State Well No. 6/26 - 19A

STATE OF OREGON MAY 17 1968 State Well No. 6/26 - 19A

(Please type or print)

(Do not write above Fina TE ENGINEER

(Bo not write above Fina TE ENGINEER

(A) SALE MA SREGON Permit No. G5993

(1) OWNER:	(11) LOCATION OF WELL:			
Name GEORGE HYBERTSEN	County MARION Driller's well nur	nber		
Addre 1867 CHELAN N. E. SALEM, OREGON	14 14 Section 7 T8 T. 65	R. 2	WEST	W.M.
(0) MYDE OF WORK (-11-).	Bearing and distance from section or subdivision	corner		
(2) TYPE OF WORK (check):				 .
New Well Deepening Reconditioning Abandon Abandon				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven Democite Definition Description	(12) WELL LOG: Diameter of well be	elow casi	ng	
Cable A Jetted [Domestic Industrial Manietpar	Depth drilled 130 ft. Depth of comple	ted well	130	ft.
Dug	Formation: Describe color, texture, grain size a	nd struct	ure of m	aterials;
(5) CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum with at least one entry for each change of forms	tion. Re	port each	change
Diam. from 0 ft. to 130 ft. Gage 250	in position of Static Water Level as drilling prod	eeds. No	ote drillir	ig rates.
ft. Gage ft. Gage	MATERIAL	From	То	swL
" Diam. from	TOP SOIL	0	3	
PERFORATIONS: Perforated? F Yes 🗆 No.	BROWN OLAY	3	25	
Type of perforator used MTLLS	BROWN SAND	25	3 0	
Size of perforations 3/8 in. by 3 in.	BLUE OLAY	30	- 55	
780 perforations from 94 ft. to I28 ft.	GREY SAND	55	- 65	
perforations fromft. toft.	BLUE GLAY	65	- 85	
perforations from ft, to ft.	BLACK SAND	85	- 90	
perforations from ft. to ft.	GRAVEL	-90	130	
perforations from ft. to ft.				
(E) CORENIC.				
(7) SCREENS: Well screen installed? ☐ Yes ★ No				
Manufacturer's Name TypeModel No				
Diam. Slot size Set from ft. to ft.	1			
Diam. Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.				,
ft. below land surface Date 5/11/68				
Artesian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ✓ Yes ☐ No If yes, by whom? STETTLER! S			7.460	<u> </u>
d: 400 gal./min. with 48 ft. drawdown after I hrs.	Work started PRTL 17 19 68 Complete	*d 5/I	5/68	19
. 600 " 78 " I "	Date well drilling machine moved off of well	<u> </u>		¹⁹ 68
n n n	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di rials used and information reported above	rect sup	ervision	. Mate-
	knowledge and belief.	/ m	i de lo i	10
Artesian flow g.p.m. Date Temperature of water 4 Was a chemical analysis made? Yes 1 No	[Signed] / June 1888	Date //	ay15	. 1968.
Temperature of water 4 Was a chemical analysis made? Yes 1 No	(Drilling Machine Operator)		7	•
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	T7 9)	
Well seal-Material used PUDDLE CLAY				
Depth of seal 20 ft.	Water Well Contractor's Certification:	iation as	ad this s	onort is
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisd true to the best of my knowledge and beli	ef.	ia mis i	ebore is
Were any loose strata cemented off? Yes M No Depth	NAME J.F. TERRELL			
Was a drive shoe used? A Yes No	(Person, firm or corporation)	(Тур	e or print	ı
Did any strata contain unusable water? Yes No	AddressRT # I. BOX 57. GERVAIS.	OREGO)N	
Type of water? depth of strata	m. 2 h	1	1	001
Method of sealing strata off	[Signed] (Water Well Contract	le !	lere	
Was well gravel packed? Yes XXo Size of gravel:		2	. 10	1
Grevel placed from ft. toft.	Contractor's License No. 460 Date	1 jay	L. [],	19 60