NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON \$7310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON DEC 9 1974 State Well No. 45 IW-II da

(Please type or prin STATE ENGINEER State Permit No. (Do not write above this \$40 EM. OREGOII

| (1) OWNER:   | (10) LOCATION OF WELL:  |                 |  |
|--|---|-----------------|--|
| Name Richard Jink  | County Marion Driller's well number   |                 |  |
| Address Rt. 3 Eox 631  | NE ¼ SE ¼ Section 11 T. 4S  | R. 1W W.M.      |  |
| Aurora, Oregon 97002   | Bearing and distance from section or subdivision  | on corner       |  |
| (2) TYPE OF WORK (check):  |   |                 |  |
| New Well 🕅 Deepening 🗌 Reconditioning 🗋 Abandon 🗎  |   |                 |  |
| If abandonment, describe material and procedure in Item 12.  | (11) WATER LEVEL: Completed w   | ell.            |  |
| (3) TYPE OF WELL: (4) PROPOSED USE (check):  | Depth at which water was first found 20 ft.   |                 |  |
| Rotary Driven Domestic R Industrial Municipal  | Static level 70 ft. below land s  |                 |  |
| Cable   Jetted   |   |                 |  |
| Dug  | Artesian pressure lbs. per square   | a inch. Date    |  |
| CASING INSTALLED: Threaded \( \text{\text{W}}\) Welded \( \text{\text{W}}\) Welded \( \text{\text{W}}\) \( \text{Threaded}\) \( T | (12) WELL LOG: Diameter of well below casing  |                 |  |
| PERFORATIONS: Perforated?  Yes No.   | and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. |                 |  |
| Type of perforator used  | MATERIAL  | From To SWL     |  |
| Size of perforations in. by in.  | Topsoil   | 0 3             |  |
|  | Clay-brown  | 3 20            |  |
| perforations from ft. to ft   | Clay-br-sandy   | 20 30           |  |
| perforations from ft. to ft.   | Clay-brown  | 30 60           |  |
| perforations from  | Sand-brown  | 60 90           |  |
| (7) SCREENS: Well screen installed? ☐ Yes ☑ No   | Clay-blue   | 90 105          |  |
| Manufacturer's Name  | Sand-black  | 105 108         |  |
| Type Model No  | Gravel-med-sand-blck-water  | 108 116         |  |
| Diam Slot size Set from ft. to ft.   | Clay=br-sticky  | 116 122         |  |
| Diam. Slot size Set from ft. to ft.  | Clay-blue-sticky  | 122 140         |  |
| (8) WELL TESTS: Drawdown is amount water level is  | Claystone-brown   | 140 165         |  |
| lowered below static level   | Sandstone-br-claystone-conglor  |                 |  |
| Was a pump test made?   Yes  No If yes, by whom?   | Sandstone-seams of sand-blick   | 190   230       |  |
| d: gal./min. with ft. drawdown after hrs.  | Sandstone-blck  | 230 280 70      |  |
| Air Test 125 " Total " 1 "   | claystone-br-hard   | 280   290       |  |
| " " "  | Clay-blue   | 290 300         |  |
| Bailer test gal./min. with ft. drawdown after hrs.   |   |                 |  |
| esian flow g.p.m.  |   |                 |  |
| perature of water Depth artesian flow encountered ft.  | Work started 11-20 1974 Complete  | ed 11-22 1974   |  |
|  | Date well drilling machine moved off of well  | 11-25 1974      |  |
| (9) CONSTRUCTION:  | But well drilling machine moved out of well   | 1100) 10/4      |  |
| Well seal—Material used Bentonite  Well sealed from land surface to 18 ft.  Diameter of well bore to bottom of seal 12 in.  Diameter of well bore below seal 8 in.  Number of sacks of cement used in well seal 0 sacks  Number of sacks of bentonite used in well seal 14 sacks   | This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed]   |                 |  |
| Brand name of bentonite Wilbur Ellis   | Water Well Contractor's Certification:  |                 |  |
| Number of pounds of bentonite per 100 gallons of water   | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.   |                 |  |
| Was a drive shoe used? K Yes □ No Plugs Size: location ft.   | Name S & M Drilling & Supply, Inc. (Person, firm or corporation)  |                 |  |
| Did any strata contain unusable water?  Yes X No   | Address 399 SE Walnut Street Canby, Oregon  |                 |  |
| Type of water? depth of strata   | Address 222 Mar. 119 Mar. Dur. 1884   | .va.my.,vr.egon |  |
| Method of sealing strata off   | [Signed] / Mille / Mag.   |                 |  |
| Was well gravel packed?   Yes No Size of gravel:   | (Water Wen Contr  | actor)          |  |
| Gravel placed from ft. to ft.  | Contractor's License No497 Date   | 12-2 , 1974     |  |