NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT,

State Well No. ...Q.S State Permit No.

SALEM, OREGON 97310
within 30 days from the date
of well completion. WATER RESOURCES DEPT.

WATER RESOURCES DEPARTMENT,

JUL 2 3 1979 (Please type or print)

MATER RESOURCES DEPT.

	SALEM. OREGON	Total Control of the			
(1) OWNER:	SALEM. OKEGUN	(10) LOCATION OF WELL:			
Name Raymond S. Elliott		County Marion Driller's well number 2119			
Address 5670 Quince	I -	14 14 Section 20 T. 6S R. 2W W.M.			
Brooks, OR	97305	Bearing and distance from section or subdivi	sion corne	r	
(2) TYPE OF WORK	(check):				
New Well 🕻 Deepening 🛚	Reconditioning Abandon				
If abandonment, describe mate	rial and procedure in Item 12.	(11) WATER LEVEL: Completed	well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		Depth at which water was first found 57 ft.			
Rotary X Driven [	Domestic   Industrial   Municipal	Static level 23 ft. below land		Date 1/	
Cable	Irrigation X Test Well  Other				
CASING INSTALLED: Threaded Welded X  6 "Diam from top tt to 100 ft Gage .250  "Diam from ft to ft Gage		(12) WELL LOG: Diameter of well below casing			
	ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each strat	and structure	ture of n	naterials;
DEDEOD A STONE		with at least one entry for each change of form	ation. Rep	ort each o	hange in
PERFORATIONS:	Perforated? Nes 🗆 No.	position of Static Water Level and indicate pr	incipal wa	ter-bearin	g strata.
1.	11s Knife	MATERIAL	From	То	SWL
Size of perforations ½	in. by 2 in.	Topsiol	0	2	
•	om 90 ft. to 98 ft.	Brown Clay	2	38	
<del>-</del>	om ft. to ft.	Gray Clay	38 57	57 59	
perforations fro	om ft. to ft.	Black Sand and Gravel.cl	<del></del>	67	
(7) SCREENS: We	ll screen installed? 🗌 Yes 🏌 No	Brown Sand and Gravel.	ev J	07	
Manufacturer's Name	<b>*-</b>	Cemented	67	94	
Type	Model No	Brown Sand and Gravel	94	100	
	Set fromft. toft.				
Diam Slot size	Set from ft. to ft.				
(8) WELL TESTS:	Drawdown is amount water level is lowered below static level				
Was a pump test made? 🗌 Ye	s 🕅 No If yes, by whom?				
Yield: gal./min.	with ft. drawdown after hrs.				
rtest 100 Gpm	for a period of 1 hour		_		
<i>n</i> ,	и. и				
Bailer test gal./mi	n. with ft. drawdown after hrs.		1		
Artesian flow	g.p.m.				
perature of water Dep	pth artesian flow encountered ft.	Work started 1/20/78 19 Comple	ted 1/	20/78	19
(9) CONSTRUCTION:		Date well drilling machine moved off of well	1/	20/78	19
Well seal—Material used	ortland Cement	Drilling Machine Operator's Certification	l:		
Well sealed from land surface toft.		This well was constructed under my			
Diameter of well bore to bottom of sealin.		Materials used and information reported   best knowledge and belief.	i above a	are true	w my
Diameter of well bore below seal		[Signed] John W. Date 1/20/7819			
Number of sacks of cement used in well sealsacks		Drilling Machine Operator's License No			
How was cement grout placed? Poured in from the top		Drining Machine Operator's License No.	************		
· · · · · · · · · · · · · · · · · · ·		Water Well Contractor's Certification:			
. 3		This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? X Yes \( \subseteq \) No Plugs Size: location ft.		true to the best of my knowledge and belief.			
Did any strata contain unusable water?   Yes   No		NameWillamette Drilling Co. (Person, firm or corporation) (Type or print)			
Type of water? depth of strata		Address 1450 Barnick Rd. NE Salem ORegon			
Method of sealing strata off		0.11201			
Was well gravel packed? ☐ Yes X No Size of gravel:		[Signed] (Water Well Contractor)			
Gravel placed fromft. toft.		Contractor's License No. 561 Date		/78	10
		Date Date			, IU