

RECEIVED

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

4260
97310

WATER WELL REPORT APR 2 1975

STATE OF OREGON STATE ENGINEER

State Well No. 65/2W-20da

(Please type or print)

SALEM, OREGON

State Permit No.

(Do not write above this line)

G 6891

(1) OWNER:

Name Robert Zielinskie
Address 294 Juedes N.
Salem, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

12" Diam. from top ft. to 160 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mills Blade
Size of perforations 7/16 in. by 2 3/4 in.
592 perforations from 75 ft. to 112 ft.
448 perforations from 132 ft. to 160 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Driller
Yield: 300 gal./min. with 5 ft. drawdown after 4 1/2 hrs.
400 gal./min. with 7 ft. drawdown after same hrs.
500 " " 10 " " same "
600 " " 12 " " same "
700 " " 15 " " same "
800 " " 18 " " same "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 11 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 1880
1/4 1/4 Section 20 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 56 ft.
Static level 21 ft. below land surface. Date 3-29-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 160 ft. Depth of completed well 160 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Top Soil	0	2	
Brown silty Clay	2	44	
Blue Silty Clay	44	56	
Brown sand and small gravel	56	69	
Large Brown sand & gravel	69	87	
Cemented brown sand & gravel	87	114	
Gray Silty Clay Sticky	114	127	
Black sand and gravel	127	141	
Cemented black sand & gravel	141	157	
Cemented brown sand and gravel	157	160	

Work started 3-11-75 19 Completed 3-29-75 19
Date well drilling machine moved off of well 3-31-75 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Dallas L. Beier Date 3-31-75, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE Salem, Oregon 97303

[Signed] Emil O. Beier
(Water Well Contractor)

Contractor's License No. 2 Date 3-31-75, 19