

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

MAR 4 2 58 4

WATER WELL REPORT

RECEIVED AUG 13 1968

STATE OF OREGON STATE ENGINEER (Please type or print) SALEM OREGON Do not write above this line

State Well No. 6/2w-21 P State Permit No. G-4496

STATE ENGINEER SALEM OREGON JUL 25 1968

(1) OWNER:

Name A. J. Harris Address 7816 Lakeside Drive Salem, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [x] 8" Diam. from top ft. to 80 ft. Gage 250

PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used Mills Size of perforations 3/8 in. by 2 in. 208 perforations from 79 ft. to 56 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 15 ft. below land surface Date 7-17-68 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 75 gal./min. with 0 ft. drawdown after 1 hrs. Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used Drill cuttings & Puddle clay Depth of seal 20 ft. Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [x] Yes [] No Did any strata contain unusable water? [] Yes [x] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1535 1/4 Section 29 T. 6S R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing Depth drilled 80 ft. Depth of completed well 80 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Brown Clay, Brown Sand, Brown Clay and gravel, Brown sand and gravel.

Work started July 11, 1968 Completed July 16, 1968 Date well drilling machine moved off of well July 17, 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Lyle Beckthold (Drilling Machine Operator) Date 7-17-68, 19

Drilling Machine Operator's License No. 151

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)

Address 7641 55th Ave. NE Salem, Oregon 97303

[Signed] Emil O. Beier (Water Well Contractor)

Contractor's License No. 2 Date 7-17-68, 19