

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

APR 7 1969

STATE OF OREGON

State Well No. 6/2W-21

STATE ENGINEER, SALEM, OREGON 97310

(Please type or print)

within 30 days from the date of well completion.

(Do not write above this line)

State Permit No. G-4911

(1) OWNER:

Name Fred Pugh
Address 6995 Labish Center Road, Brooks, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
10" Diam. from 0 ft. to 180 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mills
Size of perforations 900 2 in. by 3/8 in.
900 perforations from 100 ft. to 179 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 25 ft. below land surface Date
Atmospheric pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Driller
Yield: 450 gal./min. with 35 ft. drawdown after 25 hrs.
500 " " 40 " " 25 "
" 550 " " 50 " " 25 "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Drill cuttings, Puddle Clay
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1376
1/4 Section 21 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing
Depth drilled 180 ft. Depth of completed well 180 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top Soil	0	3	
Brown Clay	3	20	
Brown Sandy Silt	20	55	
Gray Clay	55	60	
Gray Clay Black sand	60	90	
Black sand and Gravel	90	100	
Gray clay sand & Gravel	100	110	
Brown clay sand & gravel	110	125	
Gray clay Black sand, Gravel	125	145	
Black sand & Gravel	145	155	
Gray clay and gravel	155	180	25

Work started Feb. 17, 69 Completed 3-24-69 19
Date well drilling machine moved off of well 3-25-69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Lyle Beckwith Date 3-25-69, 19...
(Drilling Machine Operator)

Drilling Machine Operator's License No. 151

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print)
Address 7641 35th Ave. NE Salem, Oregon 97303
[Signed] Emil D. Beier
(Water Well Contractor)
Contractor's License No. 2 Date 3-25-69, 19...