NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

Gravel placed from ..... ft. to ..... ft.

WATER WELL REPORT

WATER WELL REPO
WATER RESOURCES DEPARTMENT C F V STEE OF OREGON
SALEM, OREGON 97310
within 30 days from the date
of well completion.

JUN 4 198600 not write above this time.

4 198(po not write above this line)

State Permit No.

WATER RESOURCES DEPT	·
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:
Name Gary Horrin	County Marion Driller's well number 2366
Address 3815 Quinaby Rd. N.E.	NW 1/4 NE 1/4 Section 22 T. 6S R. 2W W.M.
Salem, Oregon 97303	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 35 ft.
Rotary Driven Domestic Industrial Municipal	Static level 3 ft. below land surface. Date 6/2/81
Cable  Jetted  Irrigation  Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded W 157 gt. Gage .250	(12) WELL LOG: Diameter of well below casing
	Depth drilled 157 ft. Depth of completed well 157 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
v) PERFORATIONS: Perforated? ₩ Yes □ No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Mills Knife	MATERIAL From To SWL
Size of perforations $3/8$ in. by $2\frac{1}{4}$ in.	Topsoil 0 1
584 perforations from 95 ft. to 155 ft.	Yellow Clay 1 35
perforations from ft. to ft.	Brown Sand and Gravel 35 45
perforations from ft. to ft.	Brown Cemented Gravel 45 60
(7) SCREENS: Well screen installed?   Yes   No	Black Sand and Gravel 60 63
(1) SCREENS: Well screen installed? ☐ Yes ☒ No Manufacturer's Name	Blue Clay 63 88  Black & Cemented Gravel 88 157
Type Model No.	Black X Cemented Gravel 88 157
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(O) THEFT I MERCING. Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? No If yes, by whom? driller	
d: 400 gal./min. with 100 ft. drawdown after 6 hrs.	
n h n	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 5/8/81 19 Completed 6/2/81 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6/2/81 19
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal12 in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Grand W. Motton Date 6./2/81, 19
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No
How was cement grout placed? pumped in thru conductor	Drining Machine Operator's Incense No
pipe	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🗓 Yes 🗌 No Plugs Size: location ft.	Name WILLAMETTE DRILLING CO.
Did any strata contain unusable water? 🗌 Yes 💢 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 7365 O'Neil Rd. N.E. Salem, Oregon 9730
Method of sealing strata off	Issumed Dellas & Rosis
Was well gravel packed? ☐ Yes X No Size of gravel:	[Signed]
Gravel placed from ft. to ft.	Contractor's License No. 561 Date 6/2/81 , 19