

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

434 MARI.

STATE OF OREGON (Please type or print)

AUG 9 1974

State Well No.

65/2W-22

STATE ENGINEER

State Permit No.

SALEM, OREGON

6 6961

(1) OWNER:

Name W. E. Biggins Address 7215 Labish Center Road NE Salem, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [x] Test Well [ ] Other [ ]

CASING INSTALLED:

8" Diam. from top ft. to 121 ft. Gage 250

PERFORATIONS:

Type of perforator used Mills Size of perforations 3/8 in. by 2 in. 264 perforations from 95 ft. to 120 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [ ] No If yes, by whom? Driller Yield: 100 gal./min. with 10 ft. drawdown after 2 hrs. 200 " 20 " same" 300 " 35 " same"

(9) CONSTRUCTION:

Well seal—Material used Cement Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 8 sacks Number of sacks of bentonite used in well seal Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [x] Yes [ ] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 1849 1/4 1/4 Section 22 T. 6S R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 70 ft. Static level 45 ft. below land surface. Date 8-7-74 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 121 ft. Depth of completed well 121 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Yellow Clay, Brown sand and gravel, Cemented gravel.

Work started July 29, 1974 Completed Aug. 7, 1974 Date well drilling machine moved off of well Aug. 8, 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Donald W. Norton Date 8-8-74, 19... (Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE Salem, Oregon

[Signed] Emil O'Brien (Water Well Contractor)

Contractor's License No. 2 Date 3-8-74, 19...