NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT EIVED

(Please type or print)

(Please type or print)

(Do not write above WATER RESOURCES DEPT. Permit No. 6.9603

			
(1) OWNER:	(10) LOCATION OF WELL:		
Name Max M. Bibby	County Marion Driller's well number 2040		
Address 6826 Labish Cepter Rd. NE 97303	1/4 1/4 Section X 22 T. 6S R. 2W W.M.		
Salem, Oregon 97303	Bearing and distance from section or subdivision corner		
2) TYPE OF WORK (check):			
New Well 🕅 Deepening 🗌 Reconditioning 🖺 Abandon 🖺			
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 63 ft.		
otary 💢 Driven 🗆 Domestic 🗋 Industrial 🗎 Municipal 🗀	Static level 39 ft. below land surface. I	Date 5/17/77	
oug 🛘 Bored 🖟 Irrigation 🕱 Test Well 🖂 Other 🖂	Artesian pressure lbs. per square inch. I	Date	
CASING INSTALLED: Threaded \(\bar{\text{W}} \) Welded \(\bar{\text{W}} \) 10 \(\bar{\text{K}} \)" Diam from top ft. to 140 ft. Gage 250	Depth drilled 140 ft. Depth of completed well 140 ft.		
PERFORATIONS: Perforated? 🛚 Yes 🗆 No.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
ype of perforator used Mills Knife	MATERIAL From	To SWL	
ize of perforations 3/8 in. by 2 3/4 in.	Topsoil 0	3	
100 perforations from 87 ft. to XX 95 ft.	Brown Clay 3	63	
310 perforations from 115 ft. to 135 ft.	Brown Sand and Clay 63	76	
perforations from ft. to ft.	Brown Sandy Gravel 76	84	
7) SCREENS: Well screen installed? I Ves X No	Cemented Brown Sand and Gravel 84	96	
(1) SCREENS: Well screen installed? ☐ Yes 🛱 No Ianufacturer's Name	Brown Clay 96	112	
bypeModel No	KXXXX Sand and Gravel 112	138	
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.	Black Sand and Gravel, Cemented	140	
8) WELL TESTS: Drawdown is amount water level is		140	
lowered below static level			
Was a pump test made? K Yes □ No If yes, by whom? driller			
field: 150 gal./min. with 11 ft. drawdown after 1 hrs.			
450 " 42 " 1 "			
" " "			
gailer test gal./min. with ft. drawdown after hrs.			
rtesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 5/14/77 19 Completed 5/17/77 19		
9) CONSTRUCTION:	Date well drilling machine moved off of well 5/18	3/77 19	
Vell seal—Material used Portland Cement	Drilling Machine Operator's Certification:		
Vell sealed from land surface toft.	This well was constructed under my direct supervision.		
liameter of well bore to bottom of seal17 in.	Materials used and information reported above are true to my best knowledge and belief.		
plameter of well bore below seal10 in.	[Signed] Dallas & Delli Date 5/18/7719		
Sumber of sacks of cement used in well seal	(Drilling Machine Operator) Drilling Machine Operator's License No. 75.2		
fow was cement grout placed? poured in from the top	Drilling Machine Operator's License No124		
,	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
/as a drive shoe used? 🛣 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief. Name Willamette Drilling Co.		
id any strata contain unusable water? 🗌 Yes 🛣 No	Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)		
ype of water? depth of strata	Address 1450 Barnick Rd. NE Salem, Oregon 97303		
lethod of sealing strata off	I simual Palla of Don's		
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed] Sullas J. Sulls (Water Well Contractor)		
Gravel placed fromft. toft.	F/)		
		,	