WATER WEI of this report are to be filed with the State Well No. . (Please type of That ENGINEER Permit No. STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the dat (Do not write above this fine EM. OREGON of well completion. (1) OWNER: (10) LOCATION OF WELL: Name Neil Kurth County Marion Driller's well number Address8105 65th NE 1/4 Section 22 W.M T. 6S Salem Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Deepening Reconditioning Abandon New Well R If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🔲 Domestic Industrial | Municipal | Static level ft. below land surface. Date 4-2-73 Cable Jetted Dug Irrigation Y Test Well | Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [Welded 1 (12) WELL LOG: Diameter of well below casing .. 8 "Diam from top ft to 111 ft Gage 250 Depth drilled ft. Depth of completed well " Diam, from ft, toft. Gage Formation: Describe color, texture, grain size and structure of materials; ..." Diam. from ft. to ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes | No. Type of perforator used Mills MATERIAL Size of perforations 3/8 in. by Top soil. Brown perforations from 46 ft. to Brown silty Clay 32 72 perforations from 100 ft. to 106 ft. Brown gravelly clav ... perforations from ... Dark Brown gravel some clav Gray gravelly Clay with sand 75 stri (7) SCREENS: Well screen installed? Yes No Black sand and gravel some Manufacturer's Name Model No Diam. Slot size Set from ft. to Diam. Slot size Set from ft. to ft. Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? No If yes, by whom? Driller gal./min. with 8 ft. drawdown after 80 <u> 2</u> hrs. 120 9 same " 300 Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. erature of water Depth artesian flow encountered ft. Work started 19 3-22-73 Completed Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Cement and Puddle Clay This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to _____20 best knowledge and belief. Diameter of well bore to bottom of seal ... 12 Their Date 4-10-73, 19..... Diameter of well bore below seal _____8 in. (Drilling Machine Operator) Number of sacks of cement used in well seal ...9 Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? 🕱 Yes 📋 No Plugs Size: location Name WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print) Did any strata contain unusable water?

Yes X No depth of strata Address 7641 35th Ave. NE Salem, Oregon 97303 Type of water? Method of sealing strata off Was well gravel packed?

Yes
No Size of gravel: Gravel placed from ft. to Contractor's License No.2 Date 4-10-73 , 19.....

NOTICE TO WATER WELL CONTRACTOR
The original and first copy