State Well No. ..

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 TE ENGINFATE OF OREGON within 30 days from the date of well completion.

SALEM. OREGOPIE se type or print) G-3625

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static lev	rater leve	ıl is
Name MILO RAY KLIEWER	Was a pump test made? We Yes No If yes, by whom		LLER
Address RT.2 BOX 458 SALEM, OREGON.	Yield: IOO gal./min. with II ft. drawdown		hrs.
	" I 65 " I 9 "		2 "
(2) LOCATION OF WELL:	<u>" 205 " 28 "</u>		<u>"</u>
TTCV	Bailer test gal./min, with ft. drawdov	wn after	hrs.
99 & C 9 W	Artesian flow g.p.m. Date		
	Temperature of water Was a chemical analysis m	ade? 🔲 🖰	Yes □ No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below cas	ing	
	Depth drilled 125 ft. Depth of completed well	I	25 ft.
	<u> </u>		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	ne mater ange of	ial in each formation.
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL	0	3
New Well Deepening Reconditioning Abandon	YELLOW CLAY	3	IO
andonment, describe material and procedure in Item 12.	BROWN CLAY	IO	I8
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BROWN FINE SAND	I8	56
Rotary O Driven O	BROWN SAND & GRAVEL LOTS OF		
Domestic industrial Municipal Cable Jetted	SAND	56	72
Irrigation	GRAY CLAY	72	84
(6) CASING INSTALLED: Threaded Welded X	BLACK SAND	84	90
· · · · · · · · · · · · · · · · · · ·	BLACK SAND & GRAVEL	90	I03_
8 " Diam. from TOP ft. to T25 ft. Gage 250	BLACK SAND & GRAVEL WITH BROW	N	
"Diam, fromft. toft. Gage	CLAY	I03	I09
(T) PYPTOP 1 TYOUG	BLACK SAND & GRAVEL	I09	II8
(7) PERFORATIONS: Perforated? ■ Yes □ No	BROWN SAND & GRAVEL	_II8	I25
Type of perforator used MILLS			
Size of perforations 3/8 in. by 2 in.			
310 perforations from ft. to ft.		<u> </u>	!
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			_
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ▼No			
Manufacturer's Name			
Model No		ļ	
Dam Slot size Set from ft. to ft.	Work started JULY 27 19 66 Completed AU	G.3	19 6
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well AUG.		19 6
(9) CONSTRUCTION:			
	(13) PUMP:		
Well seal—Material used in seal CEMENT & PUTTLE CLAY	Manufacturer's Name		
Depth of seal ft. Was a packer used?	Type: H.P		
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? \square Yes $\ \square$ No $\ $ Depth			
Was a drive shoe used? ▼ Yes □ No	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? Yes No Size of gravel:			
Gravel placed from ft. to ft.	NAME WILLAMWITE DRILLING CO.		+)
Did any strata contain unusable water? Yes No	DE 2 BOY 276 SATEM OPEC	pe or prin	L)
Type of water? depth of strata	Address Alex Box 270 DADFAN, Otta		•••••
Method of sealing strata off	Drilling Machine Operator's License No	474	************
(10) WATER LEVELS:	6 . 1 B R.	.)	
Static level 25 st heleve land sumface 8/2 3/66	[Signed] Conul C. Water Well Contractor)	Z	
Static level 11. below land surface Date	2 AUG.3	;	66
Artesian pressure lbs. per square inch Date	Contractor's License No Date		, 19. 66