MAR (44)

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGONOV 2 2 1965 within 30 days from the date of well completion. EWATER WELL REPORT

State Well No.

STATE OF OREGON (Please type or print)

of wen completion. STATE ENGINEER	6-4240 State Permit No.	************
(1) OWNER: SALEM OREGON Name Edger Schaap	(11) WELL TESTS: Drawdown is amount water level is lowered below static level  Was a pump test made?  Yes  No If yes, by whom?	
Address Rt 2. Box 230	Yield: 250 gal./min. with 28 ft. drawdown after T	
Silverton Oregon	"550 " 30 " 2½	hrs.
	" " " " " " " " " " " " " " " " " " " "	" "
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after	hrs.
County Marion Driller's well number	Artesian flow g.p.m. Date	
1/4 1/4 Section T. R. W.M.	Temperature of water Was a chemical analysis made?  Yes	- PK NT-
Bearing and distance from section or subdivision corner		ES 110
2350 ft, N, 2500 ft, M, from S, E, cor of sec 24, T, 6, 5. R, 2W of W, M.	(12) WELL LOG: Diameter of well below casing	)ft.
	Formation: Describe by color, character, size of material and structu show thickness of aquifiers and the kind and nature of the material stratum penetrated, with at least one entry for each change of for	
	The second was a second one energy for each change of for	====
(a) myne of monic (1 - 1).	MATERIAL FROM	TO
(3) TYPE OF WORK (check):  Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Top Soil brn	<del>I</del> —
bandonment, describe material and procedure in Item 12.	Clay brn I	20
(4) PROPOSED USE (check): (5) TYPE OF WELL:	77-	50
Domestic   Industrial   Municipal   Rotary   Driven		55
Cable 24 Jetted	Packed sand brn 65	92
Test well   Other   Dug   Bored	Med congl brn w.b. 92	30
(6) CASING INSTALLED: Threaded   Welded		35
10 "Diam. from 0 ft, to 200 ft. Gage 279	Mad a 3	60
	Loose gravel w.b. I60	65
	Mah annu Thur	20Í
(7) PERFORATIONS: Perforated?   Yes □ No  Type of perforator used Mills  Size of perforations 3/8 in. by 4 in.  106.7 perforations from 102 ft. to 19.7 ft.  perforations from ft. to ft.		
perforations from ft. to ft.		
perforations fromft. toft.		
perforations from ft. to ft.		
periorations from		<del></del>
(8) SCREENS: Well screen installed? Yes X No		
Model No.		
am. Slot size Set from ft. to ft.		<del>, -</del> .
Diam Slot size Set from ft. to ft.	Work started Oct, 9 1965 Completed Oct, 19	<sup>19</sup> 65
	Date well drilling machine moved off of well Oct. 20	<sup>1</sup> 85
(9) CONSTRUCTION:  Bentonite	(13) PUMP:	
wen sear-material used in sear	Manufacturer's Name	
Depth of seal 20 No	Type: H.P.	
Diameter of well bore to bottom of seal in.		<u> </u>
Were any loose strata cemented off? [] Yes 💆 No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? ☐ Yes ☐ No	This well was drilled under my jurisdiction and this rej	ort is
Was well gravel packed? 🗌 Yes 🛅 No Size of gravel:	true to the best of my knowledge and belief.	-
Gravel placed from ft. to ft.	NAME R Stedeli & Cone	
Did any strata contain unusable water? 🗌 Yes 🔁 No	NAME R. Stadeli & Sons (Type or print)	
Type of water? Depth of strata	Address Route, 3 Box 169, Silverton	
Method of sealing strata off	Drilling Machine Operator's License No84322	
(10) WATER LEVELS:	Collect 1.1.	**********
Static level 55 ft. below land surface Date Oct, 19	[Signed]	•••••
Artesian pressure lbs. per square inch Date	Contractor's License No. 296 Date Nov II	o 65