The original and first copy. WATER WELL REPORT of this report are to be filed with the STATE OF OREGON State Well No. 6 2W-25			
STATE OF STATE ENGINEER, SALEM, OREGON 97500 CINEER (Please type within 30 days from the date of well completions ALEM OF ON (Do not write above the control of the contro	or print)	ermit No.	
(1) OWNER:	(10) LOCATION OF WELL:		
Address R.F.D. 2 SILWERTUR ORB	County // // // Driller's 14 Section 25 T.	s well number 6, S R. 2, less W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or	subdivision corner	
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 570 ft.		
Rotary Driven Domestic Industrial Municipal Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded			
/ Diam. fromft. toft. Gage	Depth drilled 225 ft. Depth of completed well 225 ft.		
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes \(\text{No.} \) Type of perforator used	position of Static Water Level and indi	cate principal water-bearing strata. From To SWL	
Size of perforations in. by in.	Soil	0 4	
perforations from 143 ft. to 127 ft.	BRIEN -Chay	24 17	
perforations from ft. to ft.	8/11/2 - // 1/21	30 05	
	BROWN - SANA	85 106	
(7) SCREENS: Well screen installed? Yes No	11 - 11 4	GRANIS 118	
Manufacturer's Name	11 - CAMMAN	120 118 143	
Type Model No Diam, Slot size Set from ft. to ft.	With College	1/2 100	
Diam. Slot size Set from ft. to ft.	BRIGATION - PRINCE AND	50 102 198	
	GRAD	1/21	
(8) WELL TESTS: Drawdown is amount water level is lewered below static level	MED, SAND	2 198 219	
Was a pump test made? Yes Tho If yes, by whom?	RING CIAN	2/9 925	
Yield: 300 gal./min. with 30 ft. drawdown after 4 hrs.	BLUR - CLAY	217 3 33	
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m. g.p.m. Depth artesian flow encountered ft.	Work started 5-26-197/	Completed (-23 - 197/	
	Date well drilling machine moved off		
(9) CONSTRUCTION:			
Well seal-Material used DRIIII6 CLAY Well sealed from land surface to 40 ft	Drilling Machine Operator's Certi This well was constructed un	der my direct supervision.	
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information a best knowledge and belief.	eported above are true to my	
Diameter of well bore below seal in.	Isigned Miller West Date 1-24797/		
Number of sacks of cement used in well seal sacks	(Drilling Marnine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 188		
Brand name of bentonite	Water Well Contractor's Certificat	ion:	
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? Yes Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name (Person, firm of corporation) (Type or print)		
Type of water? depth of strata	Address 5345	5/2/17-01-0	
Method of sealing strata off	[Signed] Harlow 7 M	Illa S'MITTE	
Was well gravel packed? [] Yes [No Size of gravel:	(Water	Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 3.7	Date	