File Original and First Copy with the STATE ENGINEER, SALEM, OREGON WARL

WATER WELL REPORT STATE OF OREGON G-6/46

State Well No. 6/2w-25Q(1)

State Permit No. .

	<u> </u>			
(1) OWNER:		(11) WELL TESTS: Drawdown is amount water lowered below static level	· level is	
Name JENSUN BROS.		Was a pump test made? X Yes \(\Boxed{\text{N}}\) No If yes, by whom?		
Address RTE. 2		Yield: 500 gal./min. with 6/ ft. drawdown aft		
SILYERTON, OREGON		n n	**	
(2) LOCATION OF WELL:		33 11 11 11 11 11 11 11 11 11 11 11 11 1		
County MARION Owner's number, if any—		Bailer test gal./min. with ft. drawdown after hrs.		
¼ ¼ Section T. R. W.M.		Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner		Temperature of water 🗶 😾 Was a chemical analysis made? 🗌 Yes 🖼 No		
	S.W. Cor.	(12) WELL LOG: Diameter of well	2	
of DIL. C. 45, T. 63, R. 2 W. of W.	M.	Depth drilled / 95 ft. Depth of completed well	195 ft.	
		Formation: Describe by color, character, size of material and show thickness of aquifers and the kind and nature of the n stratum penetrated, with at least one entry for each change.	l structure, and naterial in each e of formation.	
5 Wood DC#45 is 534 12W-5.50 chains from			om TO	
(3) TYPE OF WORK (check):	6)	TOP SOIL BROWN C	1 2	
New Well Deepening Reconditioning Reconditioning	Abandon 🛘	CLAY RR	3 25	
If abandonment, describe material and procedure in Item 11.		CLAY BLUE 33	1 24 -	
		CIAV RR 45		
PROPOSED USE (check): (5) TYPE O	F WELL:	CLAY GREY 60		
Domestic Industrial Municipal Rotary	Driven 🗌	1124 200 200 11 11 12 17	9 81	
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐	Jetted □ Bored □	LOUSEGRAVEI WR 31	90	
	Bored	MED CONGIAM WR 90		
(6) CASING INSTALLED: Threaded [Weld	ied 😿			
10 " Diam, from	e			
ft. Gage ft.		MED CONG WR 100		
	_	LOOSE GRAVEL WR 10.		
25000 27000 2000 2000 2000 2000 2000 200		HARD CONG 10	/ 84	
(7) PERFORATIONS: Perforated? MY Yes I No		SOFT CONG 12	X 133	
Type of perforator used		LOOSE GRAVEL WB 13	3 36	
SIZE of perforations 💃 in. by 3 in.		CLAY SOME GRAVEL GREY 130	0/38	
1200 perforations from	80 ft.	MED CONG WE 38	3 149	
perforations from ft. to	ft.	LUDSE SAND& GRAVEL BROWNS	9 152	
perforations from ft. to ft.		MED GONG 15	2 1.74	
perforations from ft. to	ft.	LUOSE SANDE GRAVEL BROWN 179	7 177	
perforations fromft. toft.		MED CONG BROWN 17	7 181	
		CLAY GREY 18	1 95	
(8) SCREENS: Well screen installed \square Ye	s 🔰 No	HIT GREYCLAYSTONS		
Manufacturer's Name		AT 19.	5	
Type Model No				
Slot size Set from ft, to	ft.			
Di Slot size Set from ft. to ft.		Work started 5/ /8 19 62 Completed 6/	4 1963	
(9) CONSTRUCTION:		(13) PUMP:		
Was well gravel packed? ☐ Yes ☒ No Size of gravel:		Manufacturer's Name		
Gravel placed from ft. to ft.		Type: H.P.	7	
Was a surface seal provided? \mathbb{R} Yes \square No To what depth? 2.0 ft. Material used in seal— $RENTON17E$				
Did any strata contain unusable water? ☐ Yes 😾 No		Well Driller's Statement:	41-1	
Type of water? Depth of strata		This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	uns report is	
Method of sealing strata off		D STANFIL WE THE		
32 2000000		NAME K .) 402 / L) W S (Person, firm, or corporation) (Type o	·····	
(10) WATER LEVELS: Static level 36 ft. below land surface Date 6/2/62		Address RI3 BOX 169 SILVE KTON		
atorion processes lbs nor course inch. Date		Driller's well number		
A		[Signed] C. E. Stakeli		
		(Well Driller)		
Signed], 19, 19, 19		License No. 296 Date 4/30	1963	