NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

	•			
 - 35	4	6/1		7/
State Well	No.	Wide	ר עע	LO

1964

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.	STATE O	F OREGON (State Well No		<i>(0</i>		
(1) OWNER: Allan Hasleba	cher 9 1904	(11) WELL TESTS: Drawdown is amount water level is lowered below static level				
THE O DOTELOZ ST	1 KM - 631 - 26 7 1	Was a pump test made? ▼ Yes □ No If yes, by whom? Driller				
Salem, Oreg.		Yield: 450 gal./min. with 68 ft. drawdown after 6 hrs.				
		" " " " " " " " " " " " " " " " " " "				
(2) LOCATION OF WELL:		Poilor tort				
County Marion Driller's wel	l number	Bailer test gal./min, with ft. drawdown after hrs. Artesian flow g.p.m. Date				
¼ ¼ Section T.	R. W.M.	Temperature of water Was a chemical analysis made? ☐ Yes ☐ No				
2375 ft. E. and 1600 cor. of sec. 26, T.6	ft. N. of S.W.	(12) WELL LOG: Diameter of well below casing none				
W.M.	B., R.Z W. UI	Depth drilled ft. Depth of completed well ft.				
W 0144		Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c	d and stru the mater	cture, and ial in each		
		=	nange of	formation.		
(3) TYPE OF WORK (check):		MATERIAL	FROM	TO		
**	ditioning [] Abandon [Top soil brown	1	3		
andonment, describe material and proce		C7		0		
	I	Clay brn.	3	8		
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Clay sandy grey	8	70		
Domestic 🖺 Industrial 🗌 Municipal 🗌	Rotary Driven Cable X Jetted C	Oray sandy grey		10		
Irrigation 🗶 Test Well 🗌 Other 🔲	Cable X Jetted □ Dug □ Bored □	Sand fine brn.	70	95		
(6) CASING INSTALLED: Three	eaded □ Welded 🔀	TO CLERK A MELO NA 124				
	85 ft. Gage 250	Med conglomerate grey W.B.	95	II8		
"Diam. from ft. to		Loose sand & gravel grey W.H	3.118	125		
"Diam. fromft. to	It. Gage					
mlllS	orated? 🗌 Yes 💥 No	Med conglom brn. W.B.	125	185		
Type of perforator used 1		D. 44 2 2 2 1 24 121				
Size of perforations in. by 4 672 perforations from 100		Bottommed on hard basalt blk.	<u> </u>			
perforations from perforations from	•			<u> </u>		
perforations from						
perforations from				<u> </u>		
perforations from						
(9) SCPEENS.	alled? Yes No					
Manufacturer's Name						
The state of the s						
h Slot size Set from						
Diam Slot size Set from		Work started 9/I5 1964. Completed I() /9	1964		
(9) CONSTRUCTION:	· ·	Date well drilling machine moved off of well 10/9		1964		
	2 4	(13) PUMP:				
Well seal—Material used in seal Bento	UTre	Manufacturer's Name				
Depth of seal ft. Was a		Type:H.P.				
Diameter of well bore to bottom of seal		Water Well Contractor's Certification:				
Were any loose strata cemented off? Yes	No Depth					
Was a drive shoe used? MYes ☐ No Was well gravel packed? ☐ Yes ☐ No Si	iro of drawal.	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	and this	report is		
Gravel placed from ft. to	ize of gravel:					
Did any strata contain unusuable water?		NAME R. Stadeli & Sons. (Person, firm or corporation) (Type or print)				
Type of water? depth of s		Address Rt. 3 Box I69 Silverto				
Method of sealing strata off						
(10) WATER LEVELS:		Drilling Machine Operator's License No.	•			
Static level 42 ft. below land	d surface Date 0/9/64	[Signed] Gaul a. Stadeli		***********		
	are inch Date	[Signed] Value (Water Well Contractor) Contractor's License No. 290 Date 10/14		61		
Loo. per aqu	- HOLL JAKE	Contractor's License No. Date 10/14		, ₁₉ 64		