TICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 900

STATE OF OREGON SEP5 1973state Well No. US 2W-27

of well completion. (Do not write a	STATE ENGINEER Permit No		
(1) OWNER:	(10) I OCATION OF MEY		
Name Don Gregg	County Marion Driller's well number 17	<b>7</b> 0 ·	
Address 7764 Labish Center	1/ // 0.11 0.00 - 4.00		
Salem, Oregon	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision corner		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		7 12 24 + <del>12</del> +	
If abandonment, describe material and procedure in Item 12.	(11) THARMED I DEVEN CO		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.		
Rotary C Driven C	Depth at which water was first found 79	f	
Cable 🖸 Jetted 🗌   Domestic 👺 Industrial 🗋 Municipal 🗍	Static level 65 ft. below land surface. D	ate 8-29-73	
Dug	Artesian pressure lbs. per square inch. D	ate	
(b) CASING INSTALLED: Threaded  Welded	(10)		
10 "Diam from Lop ft. to 180 ft. Gage 250	(12) WELL LOG: Diameter of well below casing		
"Diam. fromft. toft. Gage	Depth drilled 180 ft. Depth of completed well	180 ft	
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structu	re of materials	
	and show thickness and nature of each stratum and aqu with at least one entry for each change of formation. Repor	ifer penetrated	
Perforated? N Yes No.	position of Static Water Level and indicate principal water	r-bearing strate	
Type of perforator used Mills	MATERIAL From	To SWL	
Size of perforations 7/16 in. by 2 3/4 in.	Brown Top Soil		
	Blue Silty Clay 4	11	
perforations from ft. toft.	Brown silty Clay		
perforations from ft. to ft.	Brown Course Sandy Clay 74	74	
	Black sand and gravel 79	79 88	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Drawn Conservation	17	
Manufacturer's Name	Diopi- n	20	
Type Model No	77 7	80	
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
d: 100 gal./min. with 7 ft. drawdown after 3 hrs.			
" 200 " 10 " same "			
" 300 " 16 " same "			
Bailer test gal./min. with ft. drawdown after hrs.			
500 26 Same Artesian flow 600 g.p.m. 30 Same			
persture of water Double extension C. Sainte			
Lt.	Work started 8-15-73 19 Completed 8-29.	<u>73 19</u>	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8,20	_73 <sup>19</sup>	
Well seal—Material used <u>Cement and Puddle Clay</u>	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct s	upervision.	
Diameter of well bore to bottom of seal14in.	Materials used and information reported above are true to my best knowledge and belief,		
Diameter of well bore below seal10. in.	l villa alla		
Tumber of sacks of cement used in well seal11 sacks	[Signed] A MS Date 8-30-73, 19 Date 8-30-73, 19		
Tumber of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No752		
Brand name of bentonite			
Jumber of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
f water lbs./100 gals.	This well was drilled under my jurisdiction and this report is		
Vas a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.		
old any strata contain unusable water? 🗌 Yes 🌃 No	Name WILLAMETTE DRI LING COMPANY (Person, firm or corporation) (Type or print)		
ype of water? depth of strata	Address 7641 35th Ave. NE Salem, Oregon 97303		
fethod of sealing strata off	O O O		
	[Signed] Mul (Seles)		
Vas well gravel packed? ☐ Yes ⊠ No Size of gravel:	(Water Well Contractor)		
ravel placed from ft. to ft.	Contractor's License No 2 Date8-30-73	19	