

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

STATE OF OREGON JUL 27 1973 State Well No. 65/2W-27aa

(Please type or print)

STATE ENGINEER

(Do not write above this line) SALEM, OREGON State Permit No. 6-613

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

G-7273

(1) OWNER:

Name DAN PALMER
Address 7301-7th Ave

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

8" Diam. from +12" ft. to 90' ft. Gage 025
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 30 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 58° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 3 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons
of water 30 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Driller's well number
1/4 1/4 Section 27 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 80 ft.
Static level 55 ft. below land surface. Date July 25, 73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 90' ft. Depth of completed well 90' ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
top Soil	0	4	
Silt	4	64	
Brown sand & coarse sand	64	72	
Coarse sand & pea gravel	72	80	55
Large to med gravel	80	90	
Clay & large gravel	90	91	

Work started July 23 19 73 Completed July 25 19 73
Date well drilling machine moved off of well July 26 19 73

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Harold Ferrell Date July, 19.....
(Drilling Machine Operator)

Drilling Machine Operator's License No. 862

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Robinsons E&A Well Drilling
(Person, firm or corporation) (Type or print)
Address 4510 Dallas Rd NW Salem Ore

[Signed] George H. Robinson
(Water Well Contractor)

Contractor's License No. 13 Date 26 July 73, 19.....