har.	", /	•	
State Well No.	6/2W	1-2	$\mathcal{S}$

State Permit No. .

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filled with the

STATE ENGINEER, SALEM, OREGON 97310

STATE OF OREGON (Please type or print)
of well completion.

(1) OWNER:  Name RONALD E. JONES	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
	Was a pump test made? XYes No If yes, by whom?	DRILLER	
Address RT. I BROOKS, OREGON	Yield: 375 gal./min. with I4 ft. drawdow	n after 4 hrs.	
(9) TOCAMION OF WELL	" 275 " IO "	4 "	
(2) LOCATION OF WELL:	<u>" 200 " 5 "</u>	4	
County MARION Driller's well number 968	Bailer test gal./min. with ft. drawdov	wn after hrs.	
14 14 Section 28 T.65 R. 2W W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis n	nade? 🗌 Yes 🔲 No	
	(12) WELL LOG: Diameter of well below ca	ising	
	Depth drilled 60 ft. Depth of completed we	ell 60 ft.	
	Formation: Describe by color character size of material	1	
	show thickness of aquifiers and the kind and nature of t stratum penetrated, with at least one entry for each ch		
		jointage of	
(3) TYPE OF WORK (check):	MATERIAL	FROM TO	
New Well X Deepening Reconditioning Abandon	TOP SOIL	0 5	
pandonment, describe material and procedure in Item 12.	<u> ULAY</u>	5 20	
	SAND	20 32	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAVEL	32 60	
Domestic   Industrial   Municipal   Rotary   Driven			
Irrigation ☐ Test Well ☐ Other     ☐ Dug     ☐ Bored ☐	·		
(A) CACTATO TAXONATA TA			
(6) CASING INSTALLED: Threaded □ Welded ☆			
8			
"Diam, fromft, toft, Gage	I :		
(7) PERFORATIONS: Perforated? Y Yes No			
Type of perforator used MILLS			
Size of perforations 3/8 in. by 2 in.			
192 perforations from 35 ft. to 57 ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations fromft. toft.			
perforations fromft. toft.			
(8) SCREENS: Well screen installed?   Yes   No			
Manufacturer's Name			
Type Model No			
Slot size Set from ft. to ft.	Work started SEPT 8 T964 . Completed SE	DOI TT TOCA	
Dram, Slot size Set from ft. to ft.	Date well drilling machine moved off of well SEPT		
(9) CONSTRUCTION:	(13) PUMP:	• TT T349 <del>T</del>	
CENTERNIE O TOTOTTE OF AND	(16) I CMII.	-	
Well seal—Material used in seal <u>CEMENT &amp; PUDDLE CLAY</u>	Manufacturer's Name	***************************************	
Depth of seal 20 ft. Was a packer used?	Type: H.P.		
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:		
Were any loose strata cemented off?  Yes No Depth			
Was a drive shoe used? Yes No	This well was drilled under my jurisdiction at	nd this report is	
Was well gravel packed?   Yes  No Size of gravel:	true to the best of my knowledge and belief.		
	NAME WILLAMETTE DRILLING CO	**->*	
Did any strata contain unusuable water?   Type of water?  Type of water?	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT.2 BOX 276 SALEM, OREGON		
Method of sealing strata off	Drilling Machine Operator's License No	79	
(10) WATER LEVELS:	To I M		
Static level 7 ft. below land surface Date 9/II/64	9/TT/61 [Signed] Comel O. Beier		
The state of the s	(Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date SEPT	II I964	