## NOTICE TO WATER WELL CONFOCURED THE original and first control of this report are to be filled with the JUN 21969 STATE OF OREGON

STATE ENGINEER, SALEM, OBEGON STATE IN CONTROL STATE of CREEN Write above this line) of well completion. SALEM OREGON

G-4902 Reflace GR-55

	- 1 1000 regarder	7/1 V	•	
(1) OWNER:	(11) LOCATION OF WELL:			
Name Mrs. Marvel Looney	County Marion Driller's well n	umher 7	397	
Address 7005 62nd Ave. Salem, Oregon			29/ 2W	W.M
	Bearing and distance from section or subdivision		2W	- **
(2) TYPE OF WORK (check):	Substitution and the substitution of Substitution	II COLLICE		
New Well   Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well	holory and		
Cable 🔀 Jetted 🗌 Domestic 🗌 Industrial 🗎 Municipal 🗍	Depth drilled 160 ft. Depth of complete			
Dug   Bored   Irrigation  Test Well   Other	Formation: Describe color, texture, grain size			
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratu	ım and aq	uifer pe	netrated
12 " Diam. from top ft. to 160 ft. Gage 250	with at least one entry for each change of form in position of Static Water Level as drilling pro-	iation. Re oceeds. N	port eacl	n change ng rates.
ft. to ft. Gage	MATERIAL	From	то	swl
	Top Soil	<del>                                     </del>	7	
PERFORATIONS: Perforated? Ves C No.	Brown clay	0	15	
Type of perforator used Mi.11s Perforated? ⊠ Yes □ No.	Brown clay and sand	15	60	
A	Brown sand and gravel	60	70	
Size of perforations $\frac{1}{4}$ in. by $2\frac{1}{2}$ in. $\frac{140}{2}$ tt. to $\frac{140}{2}$ tt.	Brown sand& mixed gravel	70	75	
36 perforations from 75 tt. to 70 ft.	Gray clay with sand	75	95	
perforations fromft, toft.	Brown sand, gravel, clay	95	140	
perforations from ft. to ft.	Black clay , sand and Wood	140	145	
perforations from ft. to ft.	Brown clay, gravel	145	160	***
(E) CODERING		-		·
(7) SCREENS: Well screen installed? ☐ Yes ☒ No				
Manufacturer's Name				
Type Model No Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.			•	
Static level 42 ft. below land surface Date 5-23-69		<b></b>		
ian pressure lbs. per square inch Date		<b>-</b>		
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Exes \( \) No If yes, by whom? Driller				
Yield: 400 gal./min. with 45 ft. drawdown after 4 hrs.	Work started April 14, 1969 Complete	ed May 2	23. 19	6 <b>9</b> 9
" " "	Date well drilling machine moved off of wellMa			19
, , , , , , , , , , , , , , , , , , ,	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di	rect supe	rvision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported above knowledge and belief.	e are tr	ue to n	ly best
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed] Le Beckthold	Date 52	26-69	. 19
(10) CONSTRUCTION:	(Drilling Machine Operator)			,
Well seal-Material used Drill cuttings, puddle Clay	Drilling Machine Operator's License No	151		
Depth of seal	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off? 🗌 Yes 🙀 No Depth	true to the best of my knowledge and belie	ef.		
Was a drive shoe used? ☒ Yes ☐ No	NAME WILLAMETTE DRILLING COM (Person, firm or corporation)	PANY	or print)	
Did any strata contain unusable water?   Yes   No				
Type of water? depth of strata	Address 7641 35th Ave. NE Saler	H. Ures	gon	••••••
Method of sealing strata off	[Signed]	ን <i>ል ስ</i> እ	7	
Was well gravel packed?  Yes  No Size of gravel:	(Water Well Contract	or)		
Gravel placed from ft. to	Contractor's License No 2 Date Me	LY 26.	.1969 1	19
······································				